

LL50-1079-MBLED 50" Ceiling Fan with Medium Base LED Light Kit

Finishes:

- Brushed Nickel with Brushed Nickel Blades (BN)
- Oil Rubbed Bronze with Oil Rubbed Bronze Blades (ORB)
- Bronze Black with Black Blades (BBLK)
- Matte Black with Matte Black Blades (MBL)
- White with White Blades (WH)


Shade: Satin white glass

Blades: 3 Plywood Blades *(To avoid fan blade warping, fan must be installed in climate controlled environment)*

Light Source Included: 2 x 120V/9W/30K/Dimmable LED A19 Lamps

Notes/Certifications/Warranty:

- 120V
- 4" Downrod
- Installation: Down Rod Only
- Contact your Lumencia rep with the fan part number and slope angle if you are mounting to a sloped ceiling – we will let you know if this fan requires further accessories to accommodate
- Lead Wire: 76"
- Pull Chain Standard
- Remote Control *(Sold Separately Part# LLRC10AC)*
- Wall Control *(Sold Separately Part#LLWC8-WH or LLWC16-WH)*
- Fans Dim with LLRC10AC or LLWC8WH Controls
- AC Motor | 153 x 15 mm motor | 3 capacitors
- Speeds: 3, Reversible
- RMP: 229 (High)/ 100 (Low)
- CFM: 5204
- Airflow Efficiency: 90
- cETLus Listed for Damp Locations *(Not for Outdoor Use)*
- Limited Lifetime Motor Warranty
- 1 Year Limited Warranty on Lamps
- All other Parts have a 1 Year Warranty



ORDERING INFORMATION


Model	Finish
LL50-1079-MBLED	BN ORB BBLK MBL WH

Downrods








LLDR 1/2" Downrod available in several sizes.

Features:

- 0.5" Diameter Downrod
- Available in 12", 18", 24", 36", 48", 60", and 72"
- Recommended 7" of clearance under ceiling fan blades



Part #	Finish
LLDR12	BN
LLDR18	BLK
LLDR24	WH
LLDR36	ORB
LLDR48	
LLDR60	
LLDR72	

Part #	Image	Speeds/ Light Control	Electrical Notes	Notes
LLRC-10-AC 3 Speed Hand-held remote control for AC motor ceiling fans		<ul style="list-style-type: none"> • 3-speed fan control - Hi, Med, Low, Off • Light control - On-Off, full-range dimming 	<ul style="list-style-type: none"> • 120V/ 60Hz • 3-wire installation • 1.5A Max Load for Ceiling Fan • 300W Max Load for Light • Compatible with LED, CFL and Incandescent Fans <p>Transmitter: Requires 9V Battery (not included)</p> <p>Receiver: 4-DIP Switches; 16 possible combination for multiple fan operation</p> <p>Not Suitable for Multi-Family Units</p>	<p>Dimensions: 4.5" L x 4.5" W x 0.87" W</p> <ul style="list-style-type: none"> • Canopy Wall Mount • White Finish • 3 Wire Installation • Use with CFL and LED Source • Maximum distance is 20 feet • UL Listed for Dry location applications • FCC Certified • 1 Year Limited Warranty 
LLWC8-WH 4 Speed Wall Control for Fans with Light Kits		<ul style="list-style-type: none"> • 4 Speed Fan Control • Full-range dimming of light 	<ul style="list-style-type: none"> • 120V/ 60Hz • 3-wire installation • Compatible with LED, CFL and Incandescent Fans 	<p>Dimensions: 1.75"W x 4.125"H 1.75"W x 4.125"H</p> <ul style="list-style-type: none"> • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations 
LLWC16-WH 3 Speed Wall Control for Fans with Light Kits		<ul style="list-style-type: none"> • 3 Speed Fan Control- Hi, Med, Low, Off • On/Off Light Control 	<ul style="list-style-type: none"> • 120V/ 60Hz • 3-wire installation • Compatible with LED, CFL and Incandescent Fans 	<p>Dimensions: 1.75"W x 4.125"H 1.75"W x 4.125"H</p> <ul style="list-style-type: none"> • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations 
LLWC13-WH 4 Speed Fan Control For Fan Only		<ul style="list-style-type: none"> • 4 Speed Fan Control 	<ul style="list-style-type: none"> • 120V/ 60Hz • Fan Load Max 1.25A Light Load Max 500W • Compatible with CFL Fans 	<p>Dimensions: 1.75" W x 4.125" H</p> <ul style="list-style-type: none"> • 3-wire installation • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations 