

## LL52-1045-ESLED Series

### 52" Energy Star Ceiling Fan with Integrated LED Light Kit.

**Finishes:**

- Brushed Nickel with Brushed Nickel Blades (BN)
- Black with Black Blades (BLK)
- Matte Black with Matte Black Blades (MBL)
- Oil Rubbed Bronze with Oil Rubbed Bronze Blades (ORB)
- White with White Blades (WH)

**Dimensions:** 52.00D x 15.25"OH

**Shade:** Satin White Glass

**Blades:** 5 Plywood Blades.

**Light Source:** 120V/16w/822lm Del@30K/90CRI/Dimmable

**Notes/Certifications/Warranty:**

- 120V
- 4" Downrod Included
- Downrod Mount Only
- Contact your Lumencia rep with the fan part number and slope angle if you are mounting to a sloped ceiling we will let you know if this fan requires further accessories to accommodate
- Lead Wire: 76"
- Pull Chain Standard
- Remote Control *(Sold Separately Part# LLRC-10-AC)*
- Wall Control *(Sold Separately Part#LLWC8-WH, LLWC16-WH)*
- AC Motor | 172 x 14 mm motor | 3 capacitors
- Speeds: 3, Reversible
- RPM: 177 (High)/ 73 (Low)
- CFM: 5224
- Airflow Efficiency: 104
- cETLus Listed for Dry Locations
- Energy Star Rated
- Title 20 Compliant
- Limited Lifetime Motor Warranty
- 5 Year Warranty on LED Light Kit
- All other Parts have a 1 Year Warranty



#### ORDERING INFORMATION


Model	Finish
LL52-1045-ESLED	BN BLK MBL ORB WH

### Downrods








LLDR 1/2" Downrod available in several sizes.

**Features:**

- 0.5" Diameter Downrod
- Available in 12", 18", 24", 36", 48", 60", and 72"
- Recommended 7" of clearance under ceiling fan blades



Part #	Finish
LLDR12	BN
LLDR18	BLK
LLDR24	WH
LLDR36	ORB
LLDR48	
LLDR60	
LLDR72	

Part #	Image	Speeds/ Light Control	Electrical Notes	Notes
<b>LLRC-10-AC</b> 3 Speed Hand-held remote control for AC motor ceiling fans		<ul style="list-style-type: none"> <li>• 3-speed fan control - Hi, Med, Low, Off</li> <li>• Light control - On-Off, full-range dimming</li> </ul>	<ul style="list-style-type: none"> <li>• 120V/ 60Hz</li> <li>• 3-wire installation</li> <li>• 1.5A Max Load for Ceiling Fan</li> <li>• 300W Max Load for Light</li> <li>• Compatible with LED, CFL and Incandescent Fans</li> </ul> <p><b>Transmitter:</b> Requires 9V Battery (not included)</p> <p><b>Receiver:</b> 4-DIP Switches; 16 possible combination for multiple fan operation</p> <p><b>Not Suitable for Multi-Family Units</b></p>	<p><b>Dimensions:</b> 4.5" L x 4.5" W x 0.87" W</p> <ul style="list-style-type: none"> <li>• Canopy Wall Mount</li> <li>• White Finish</li> <li>• 3 Wire Installation</li> <li>• Use with CFL and LED Source</li> <li>• Maximum distance is 20 feet</li> <li>• UL Listed for Dry location applications</li> <li>• FCC Certified</li> <li>• 1 Year Limited Warranty</li> </ul> 
<b>LLWC8-WH</b> 4 Speed Wall Control for Fans with Light Kits		<ul style="list-style-type: none"> <li>• 4 Speed Fan Control</li> <li>• Full-range dimming of light</li> </ul>	<ul style="list-style-type: none"> <li>• 120V/ 60Hz</li> <li>• 3-wire installation</li> <li>• Compatible with LED, CFL and Incandescent Fans</li> </ul>	<p><b>Dimensions:</b> 1.75"W x 4.125"H1.75"W x 4.125"H</p> <ul style="list-style-type: none"> <li>• Installs in a standard single-gang electrical box.</li> <li>• Wall Control must be Mounted Indoors</li> <li>• Not for Multiple Fan Control</li> <li>• cULus Listed for Dry Locations</li> </ul> 
<b>LLWC16-WH</b> 3 Speed Wall Control for Fans with Light Kits		<ul style="list-style-type: none"> <li>• 3 Speed Fan Control- Hi, Med, Low, Off</li> <li>• On/Off Light Control</li> </ul>	<ul style="list-style-type: none"> <li>• 120V/ 60Hz</li> <li>• 3-wire installation</li> <li>• Compatible with LED, CFL and Incandescent Fans</li> </ul>	<p><b>Dimensions:</b> 1.75"W x 4.125"H1.75"W x 4.125"H</p> <ul style="list-style-type: none"> <li>• Installs in a standard single-gang electrical box.</li> <li>• Wall Control must be Mounted Indoors</li> <li>• Not for Multiple Fan Control</li> <li>• cULus Listed for Dry Locations</li> </ul> 
<b>LLWC13-WH</b> 4 Speed Fan Control For Fan Only		<ul style="list-style-type: none"> <li>• 4 Speed Fan Control</li> </ul>	<ul style="list-style-type: none"> <li>• 120V/ 60Hz</li> <li>• Fan Load Max 1.25A   Light Load Max 500W</li> <li>• Compatible with CFL Fans</li> </ul>	<p><b>Dimensions:</b> 1.75" W x 4.125" H</p> <ul style="list-style-type: none"> <li>• 3-wire installation</li> <li>• Installs in a standard single-gang electrical box.</li> <li>• Wall Control must be Mounted Indoors</li> <li>• Not for Multiple Fan Control</li> <li>• cULus Listed for Dry Locations</li> </ul> 