

Job Name:		
Type:		
Part #:		
Notes:		

LL52-1071-LED LL52-1071

52" Ceiling Fan - Available with Integrated LED Light Kit

Finishes:

- Brushed Nickel with Brushed Nickel Blades (BN)
- Brushed Nickel with Walnut Blades (BNW)
- Black with Black Blades (BLK)
- Matte Black with Matte Black Blades (MBL)
- Oil Rubbed Bronze with Walnut Blades (ORBW)
- White with White Blades (WH)

Dimensions:

LL52-1074-LED: 52.00"OD x 13.00"OH **LL52-1074:** 52.00"OD x 12.25"OH

Lens: Acrylic

Blades: 4 MDF Blades.

LL52-1071-LED Light Source: 120V/15w/983lm Del@30K/90CRI/Dimmable

Notes/Certifications/Warranty:

- 120V
- 4" Downrod Included
- Downrod Mount Only
- Contact your Lumencia rep with the fan part number and slope angle if you are mounting to a sloped ceiling – we will let you know if this fan requires further accessories to accommodate
- · Lead Wire: 76"
- · Pull Chain Standard
- Remote Control (Sold Separately Part# LLRC-10-AC)
- Wall Control for LL52-1071-LED (Sold Separately Part# LLWC8 or LLWC16)
- Motor: 153 x 12mm Motor | 3 capacitors
- LL52-1071-LED RPM: 177(High)/71(Low), CFM: 4945, Airflow Efficiency: 86
- LL51-1071 RPM: 195(High)/73(Low), CFM: 4899, Airflow Efficiency: 86
- · Speeds: 3, Reversible
- Title 20 Compliant
- UL Listed
- · Limited Lifetime Motor Warranty
- 5 Year Warranty on LED Light Kit
- All Non-Elecrtical Parts have a 1 Year Warranty





ORDERING INFORMATION

Model	Finish
LL52-1071-LED LL52-1071	BN BNW BLK MBL ORBW WH



Job Name:		
Туре:		
Part #:		
Notes:		

Downrods

LLDR 1/2" Downrod available in several sizes.

Features:

- 0.5" Diameter Downrod
 Available in 12", 18", 24", 36", 48", 60", and 72"
 Recommended 7' of clearance under ceiling fan blades



Part #	Finish
LLDR12 LLDR18 LLDR24 LLDR36 LLDR48 LLDR60 LLDR72	BN BLK WH ORB

Part #	Image	Speeds/ Light Control	Electrical Notes	Notes
LLRC-10-AC 3 Speed Hand-held remote control for AC motor ceiling fans	000	3-speed fan control - Hi, Med, Low, Off Light control - On-Off, full- range dimming	120V/ 60Hz 3-wire installation 1.5A Max Load for Ceiling Fan 300W Max Load for Light Compatible with LED, CFL and Incandescent Fans Transmitter: Requires 9V Battery (not included) Receiver: 4-DIP Switches; 16 possible combination for multiple fan operation Not Suitable for Multi-Family Units	Dimensions: 4.5" L x 4.5" W x 0.87" W Canopy Wall Mount White Finish Wire Installation Use with CFL and LED Source Maximum distance is 20 feet UL Listed for Dry location applications FCC Certified Tyear Limited Warranty
LLWC8-WH 4 Speed Wall Control for Fans with Light Kits	Q 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	4 Speed Fan Control Full-range dimming of light	120V/ 60Hz 3-wire installation Compatible with LED, CFL and Incandescent Fans	Dimensions: 1.75"W x 4.125"H1.75"W x 4.125"H • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations
LLWC16-WH 3 Speed Wall Control for Fans with Light Kits		3 Speed Fan Control- Hi, Med, Low, Off On/Off Light Control	120V/ 60Hz 3-wire installation Compatible with LED, CFL and Incandescent Fans	Dimensions: 1.75"W x 4.125"H1.75"W x 4.125"H Installs in a standard single-gang electrical box. Wall Control must be Mounted Indoors Not for Multiple Fan Control CULus Listed for Dry Locations
LLWC13-WH 4 Speed Fan Control For Fan Only	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	• 4 Speed Fan Control	120V/ 60Hz Fan Load Max 1.25A Light Load Max 500W Compatible with CFL Fans	Dimensions: 1.75" W x 4.125" H • 3-wire installation • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations