

LL65-747-BLK-LED
LL65-748-ORB-LED
LL65-749-WH-LED

Mini Wall Pack in 3 Finishes with Photocell.

See Notes for Finishes

Construction: Cast Aluminum with Polycarbonate Lens

Dimensions: 8.6"H x 5.8"W x 3.1"E

Light Source: UNV/20W/80CRI/Dimmable MCT
 Selectable- 30K/40K/50K

Lumen Output: 2608lm/30K, 2920lm/40K, 2703lm/50K

Notes/Certifications/Warranty:

- UNV= Universal Voltage, 120~277V
- 0-10V Dimming
- Photocell Included-May Bypass
- Beam Angle: 100
- Surge Protection: 2.5KV
- Operating Temperature: -20°C (-4°F) to a maximum of +45°C (+113°F)
- cULus Listed for Wet Locations
- ADA Compliant
- California T24 Compliant
- IP65
- RoHS Compliant
- FCC Compliant
- 50K Life Hours
- 5 Year Limited Warranty



ORDERING INFORMATION

| Model | Notes |
|------------------|--------------------------------|
| LL65-747-BLK-LED | Wall Pack in Black |
| LL65-748-ORB-LED | Wall Pack in Oil Rubbed Bronze |
| LL65-748-WH-LED | Wall Pack in White |