

| Job Name: | | |
|-----------|--|--|
| Type: | | |
| Part #: | | |
| Notes: | | |

LLBH24DX LLBH48DX

LED Vaportite in 2' & 4' Lengths

Housing: Injection Molded Polycarbonate with High Transmission Opal Polycarbonate Shade

Dimensions:

LLBH24DX: 26.5"L x 4.3"W x 2.4"H **LLBH48DX:** 50.0"L x 4.3"W x 2.4"H

Light Source:

LLBH24DX-16W: UNV/16w/1870Im Del@40k/80CRI.
LLBH24DX-HE: UNV/23w/2510Im Del@40k/80CRI.
LLBH48DX-HE: UNV/45w/4950Im Del@40k/80CRI.
LLBH48DX-VHO: UNV/29w/3760Im Del@40k/80CRI.

Options:

- Optional Bi-Level OCS-Occupancy Sensor with Multiple Settings for Light Levels and Duration
- Optional EM Driver- Provides 8w of Battery Backup in the event of a power failure.

Certification/Warranty:

- ETL/cETL Listed
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.
- DLC Listed
- IP65 Rated







| Model # | Color Temp. | Options |
|--|----------------|---|
| LLBH24DX-16W LLBH24DX-HE LLBH48DX-HE LLBH48DX-VHO | 40K 50K | BI: Bi-Level Light Option with Built-in Motion Sensor EM: Emergency Battery Back Up |

May be available with other voltage, wattage, and finish options by special order. Please contact your Lumencia Representative for more information

