

LLCYL-5-G2

5" LED Cylinder - Available in Ceiling, Wall, and Pendant Mount

Construction: Powder Coated Aluminum
Reflector: Choice of 5 Reflectors

Finishes: Semi-Matte White (SMWH), Black (BLK), Bronze (BRZ) and Silver (SLV)


Light Source:

- 10W:** 120~277V/10W/1,000lm Beam Angle 67.7°
- 14W:** 120~277V/14W/1,400lm Beam Angle 75°
- 22W:** 120~277V/22W/2,200lm Beam Angle 75.5°


- Available in 80 or 90 CRI
- Select from 27K, 30K, 35K or 40K
- Triac/ELV – 5-100%; 120v
- 0-10V – 5-100%; 120v or 277v
- EM: Battery Backup: 9W/800lms (approx.), 90 minutes after full charge.

Notes/Certifications/Warranty:

- Operating Temperature -22° F to 104° F (-30°C to 40°C).
- Buy American Act Compliant
- cCSA-us Listed-See Trims for Location Ratings (Damp or Wet)
- 5 Year Limited Warranty on LED and Housing



Ceiling Mount



Wall Mount

Ceiling and Wall Mount Ordering Information:

PART#	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-5-G2-C <i>(Ceiling Mount)</i>	10W 14W 22W	27K 30K 35K 40K	8 9	UTD: 120~277VAC, Triac/ELV Dimming (14W & 22W Only) *TRIAC/ELV Dimming at 120V Only UZTD: 120~277VAC, 0~10V Dimming (10W, 14W & 22W)	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM
LLCYL-5-G2-W <i>(Wall Mount)</i>							

Pendant Mount Ordering Information:

PART#	PENDANT STYLE	STEM For Swivel	CABLE & CORD LENGTH	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-5-G2-P	R: Rigid Stem <i>(Select Stem Length)</i> S: Swivel Mount <i>(Select Stem Length)</i> C: Cord & Cable <i>(Select Cable and Cord Length)</i>	12" 18" 24" 36" 48"	C32: 32" C58: 58" C108: 108" C128: 128"	10W 14W 22W	27K 30K 35K 40K	8 9	UTD: 120~277VAC, Triac/ELV Dimming (14W & 22W Only) *TRIAC/ELV Dimming at 120V Only UZTD: 120~277VAC, 0~10V Dimming (10W, 14W & 22W)	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM

TRIMS



5TRMSOR
Specular Open Reflector
Damp Location Rated

5TRMBFR
Baffle w / Reflector
Damp Location Rating

5TRMBFRL-W
Baffle w / Regressed Fresnel
Lens Wet Location Rated.

5TRMSRL-W
Reflector w / Clear Collar and
Regressed Fresnel Lens. Wet
Location Rated.


* Wide beam reflector is standard. Also available in narrow beam in reflector (consult with factory).

Trim	Reflector Finish	Baffle Finish for 5TRMBFR & 5TRMBFRL-W
5TRMSOR 5TRMBFR 5TRMBFRL-W 5TRMSRL-W <small>^Select Baffle Finish for 5TRMBFR and 5TRMBFRL-W</small>	HC: Haze Clear WH: White Painted	WH White BLK Black

Approved Dimmers	
* Lutron:	
Triac:	Skylark
ELV:	NovaT NTELV-300 & Diva DVELV-300P & 303P Maestro MAELV-600 Skylark SEL-VB-300P
0-10V:	Diva DDTV Diva DVSTV-IV
CFL/LED:	Diva DVCL-253P Ariadni AYCL-253P
* Leviton:	
Triac:	Trimatron
ELV:	IPE04-1L (Acenti: ATE06-1LW
<small>* Consult tech. service or factory for additional dimmers</small>	

PHOTOMETRIC REPORT


* Contact Factory for IES File



	Illuminance at a Distance	
	Center Beam FC	Beam Width
2.0ft	147.3 fc	2.7 ft
4.0ft	36.8 fc	5.3 ft
6.0ft	16.4 fc	8.0 ft
8.0ft	9.2 fc	10.6 ft
10.0ft	5.9 fc	13.3 ft
12.0ft	4.1 fc	16.0 ft

Beam Spread: 66°

LLCYL-5-G2-14W



	Illuminance at a Distance	
	Center Beam FC	Beam Width
2.0ft	228.7 fc	2.7 ft
4.0ft	57.2 fc	5.3 ft
6.0ft	25.4 fc	8.0 ft
8.0ft	14.3 fc	10.6 ft
10.0ft	9.2 fc	13.3 ft
12.0ft	6.4 fc	16.0 ft

Beam Spread: 66°

LLCYL-5-G2-22W