

LLCYL-6-G2

6" LED Cylinder - Available in Ceiling, Wall, and Pendant Mount

Construction: Powder Coated Aluminum
Reflector: Choice of 5 Reflectors

Finishes: Semi- Matte White (SMWH), Black (BLK), Bronze (BRZ) and Silver (SLV)


Light Source:

- 10W:** 120~277V/10W/1,000lm Beam Angle 67.7°
- 14W:** 120~277V/14W/1,400lm Beam Angle 75°
- 22W:** 120~277V/22W/2,200lm Beam Angle 75.5°
- 30W:** 120~277V/30W/3,000lm Beam Angle 77°


- Available in 80 or 90 CRI
- Select from 27K, 30K, 35K or 40K
- Triac/ELV – 5-100%; 120v
- 0-10V – 5-100%; 120v or 277v
- EM: Battery Backup: 9W/800lms (approx.), 90 minutes after full charge.

Notes/Certifications/Warranty:

- Operating Temperature -22° F to 104° F (-30°C to 40°C).
- Buy American Act Compliant
- cCSA-us Listed-See Trims for Location Ratings (Damp or Wet)
- 5 Year Limited Warranty on LED and Housing



Ceiling Mount



Wall Mount


Ceiling and Wall Mount Ordering Information:

PART#	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-6-G2-C (Ceiling Mount)	10W 14W 22W 30W	27K 30K 35K 40K	8 9	UTD: 120~277VAC, Triac/ELV Dimming (14W, 22W & 30W Only) *TRIAC/ELV Dimming at 120V Only	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM
LLCYL-6-G2-W (Wall Mount)				UZTD: 120~277VAC, 0~10V Dimming (10W, 14W, 22W, & 30W)			

Pendant Mount Ordering Information:

PART#	PENDANT STYLE	STEM For Swivel	CABLE & CORD LENGTH	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-6-G2-P	R: Rigid Stem (Select Stem Length) S: Swivel Mount (Select Stem Length) C: Cord & Cable (Select Cable and Cord Length)	12" 18" 24" 36" 48"	C32: 32" C58: 58" C108: 108" C128: 128"	10W 14W 22W 30W	27K 30K 35K 40K	8 9	UTD: 120~277VAC, Triac/ELV Dimming (14W, 22W & 30W Only) *TRIAC/ELV Dimming at 120V Only	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM
							UZTD: 120~277VAC, 0~10V Dimming (10W, 14W, 22W, & 30W)			

TRIMS



6TRMSOR

Specular Open Reflector
Damp Location Rated

6TRMBFR

Baffle w / Reflector
Damp Location Rating

6TRMBFRL-W

Baffle w / Regressed Fresnel
Lens. Wet Location Rated.

6TRMSRL-W

Reflector w / Clear Collar and
Regressed Fresnel Lens.
Wet Location Rated.

6TRMWW


Wall Wash w /
Reflector Plate
Damp Location Rated

* Wide beam reflector is standard. Also available in narrow beam in reflector (consult with factory).

Trim	Reflector Finish	Baffle Finish for 6TRMSOR & 6TRMBFRL-W
6TRMSOR 6TRMBFR 6TRMBFRL-W 6TRMSRL-W 6TRMWW <i>^Select Baffle Finish for 6TRMSOR and 6TRMBFRL-W</i>	HC: Haze Clear WH: White Painted	WH White BLK Black

PHOTOMETRIC REPORT


* Contact Factory for IES File



Center Beam FC	Beam Width
2.0ft	163.9fc
4.0ft	41.0fc
6.0ft	18.2fc
8.0ft	10.2fc
10.0ft	6.6fc
12.0ft	4.6fc

Beam Spread: 63°


LLCYL-8-G2-14W



Center Beam FC	Beam Width
2.0ft	248.0fc
4.0ft	62.0fc
6.0ft	27.6fc
8.0ft	15.5fc
10.0ft	9.9fc
12.0ft	6.9fc

Beam Spread: 63°

LLCYL-8-G2-23W



Center Beam FC	Beam Width
2.0ft	348.8fc
4.0ft	87.2fc
6.0ft	38.8fc
8.0ft	21.8fc
10.0ft	14.0fc
12.0ft	9.7fc

Beam Spread: 63°

LLCYL-8-G2-30W

Approved Dimmers

*** Lutron:**

Triac: Skylark S-600
 ELV: NovaT NTELV-300 & 600
 Diva DVELV-300P & 303P
 Maestro MAELV-600
 Skylark SEL-VB-300P

0-10V: Diva DDTV

Divi DVSTV-IV

CFL/LED: Diva DVCL-253P

Ariadni AYCL-253P

*** Leviton:**

Triac: Trimatron #705W

ELV: IPE04-1L (ELV)

Aceniti: ATE06-1LW

* Consult tech. service or factory for additional dimmers