

LLCYL-8-G2

8" LED Cylinder - Available in Ceiling, Wall, and Pendant Mount

Construction: Powder Coated Aluminum
Reflector: Choice of 5 Reflectors

Finishes: Semi-Matte White (SMWH), Black (BLK), Bronze (BRZ) and Silver (SLV)

Light Source:

10W: 120~277V/10W/1,000lm Beam Angle 67.7°

14W: 120~277V/14W/1,400lm Beam Angle 75°

22W: 120~277V/22W/2,200lm Beam Angle 75.5°


30W: 120~277V/30W/3,000lm Beam Angle 77°

44W: 120~277V/44W/4,400lm Beam Angle 77°


- Available in 80 or 90 CRI
- Select from 27K, 30K, 35K or 40K
- Triac/ELV – 5-100%; 120v
- 0-10V – 5-100%; 120v or 277v
- EM: Battery Backup: 9W/800lms (approx.), 90 minutes after full charge.

Notes/Certifications/Warranty:

- Operating Temperature -22° F to 104° F (-30°C to 40°C).
- Buy American Act Compliant
- cCSA-us Listed-See Trims for Location Ratings (Damp or Wet)
- 5 Year Limited Warranty on LED and Housing



Ceiling Mount



Wall Mount

Ceiling and Wall Mount Ordering Information:


PART#	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-8-G2-C (Ceiling Mount)	10W	27K	8	UTD: 120~277VAC, Triac/ELV Dimming (14W, 22W & 30W Only) *TRIAC/ELV Dimming at 120V Only UZTD: 120~277VAC, 0~10V Dimming (10W, 14W, 22W, 30W & 44W)	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM
LLCYL-8-G2-W (Wall Mount)	14W 22W 30W 44W	30K 35K 40K	9				

*TRIAC/ELV Dimming at 120V Only

Pendant Mount Ordering Information:

PART#	PENDANT STYLE	STEM For Swivel	CABLE & CORD LENGTH	WATTS	COLOR TEMP	CRI	DRIVER	FINISH	TRIM	OPTIONS
LLCYL-8-G2-P	R: Rigid Stem (Select Stem Length) S: Swivel Mount (Select Stem Length) C: Cord & Cable (Select Cable and Cord Length)	12" 18" 24" 36" 48"	C32: 32" C58: 58" C108: 108" C128: 128"	10W 14W 22W 30W 44W	27K 30K 35K 40K	8 9	UTD: 120~277VAC, Triac/ELV Dimming (14W, 22W & 30W Only) *TRIAC/ELV Dimming at 120V Only UZTD: 120~277VAC, 0~10V Dimming (10W, 14W, 22W, 30W, & 44W)	SMWH BLK ORB SLV	Order on Page 2.	EM: Emergency Driver BIEM: Bodine Integral EM

TRIMS



8TRMSOR
Specular Open Reflector
Damp Location Rated

8TRMBFR
Baffle w / Reflector
Damp Location Rating

8TRMBFRL-W
Baffle w / Regressed Fresnel
Lens. Wet Location Rated.

8TRMSRL-W
Reflector w / Clear Collar and
Regressed Fresnel Lens.
Wet Location Rated.



8TRMWW
Wall Wash w /
Reflector Plate
Damp Location Rated

* Wide beam reflector is standard. Also available in narrow beam in reflector (consult with factory).



Trim	Reflector Finish	Baffle Finish for 8TRMSOR & 8TRMBFRL-W
8TRMSOR 8TRMBFR 8TRMBFRL-W 8TRMSRL-W 8TRMWW <i>^Select Baffle Finish for 8TRMSOR and 8TRMBFRL-W</i>	HC: Haze Clear WH: White Painted	WH White BLK Black

PHOTOMETRIC REPORT



* Contact Factory for IES File



LLCYL-8-G2-14W



LLCYL-8-G2-23W



LLCYL-8-G2-30W

○ Triac/ELV/0-10V Approved Dimmers

*** Lutron:**

Triac: Skylark S-600
 ELV: NovaT NTELV-300 & 600
 Diva DVELV-300P & 303P
 Maestro MAELV-600
 Skylark SEL-VB-300P

0-10V: Diva DDTV

Divya DVSTV-IV

CFL/LED: Diva DVCL-253P

Ariadni AYCL-253P

*** Leviton:**

Triac: Trimatron #705W

ELV: IPE04-1L (ELV)

Acanti: ATE06-1LW

* Consult tech. service or factory for additional dimmers