

## LL50971-4-30K

LED SLIM RECESSED ROUND 4"

**Construction:** Aluminum Construction with White Finish and Frosted Polycarbonate Lens.  
Junction Box and Driver Connect Included

**Dimensions:** 5.06"D x 1.00"H

**Light Source:** 120v/10w/650lm Del@30K/90CRI

**Notes/Certifications/Warranty:**

- 120V
- 110° Beam Spread
- Dimmable to 10% See List of Preferred Dimmers
- 13-inch feed wire and twist lock connector between light and driver, and powerful spring clips.
- 10' Extension Cord Available.
- IC Rated
- Not recommended for use with motion sensors, light sensors, timers or any other external controls
- ETL Listed for Damp Locations (Indoor Use Only)
- IC Rated
- RoHS Compliant
- FCC Complaint
- Energy Star Rated
- Title 24 Compliant
- 50K Life Hours
- 5 year Limited Warranty



Preferred Dimmers
<b>Eaton:</b> SAL06-LA-K
<b>Leviton:</b> 011-IPL06-10Z, 012-TSL06-1LW, 001-RDL06-10Z, 001-RNL06-10Z, 002-6674-10W, 001-DW6HD-1BZ, 001-DW1KD-1BZ, 001-DSL06-1LZ, R62-06674-P0W, R12-06672-1LW, R50-1PL06-10M
<b>Lutron:</b> DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R



**ORDERING INFORMATION**

PART #
LL50971-4-30K

Discontinued 01/13/2023  
LL50950-4-27K  
LL50990-4-40K  
LL51010-4-50K