

LL510XX/LL511XX SERIES

LED SLIM RECESSED ROUND 6"

Construction:

- Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included



Dimensions: 6.72"D x 0.98"H

See Ordering Section for Performance Notes and Energy Star/T24 Certifications.

Notes/Certifications/Warranty:

- 120V
- Available in 27k/30k/40k/50k.
- 120° Beam Spread
- Dimmable to 10%. Recommended Dimmers
 - Leviton:** CD-C22-06672-12A, CD-R00-RNL06-12
 - Lutron:** CTCL-153P-WH, DVCL-153P, DVCL-153PR-WH, DVCL-253P-WH, LGCL-153PLH, MACL-153M-WH, MACL-153PLH-WH, MRF2-6CL-WH, PD-10NXD-WH, PD-6WCL-WH, S-600P-WH, S-603PG, SCL-153P, TGCL-153P
- 26 inch lead wire between light and external driver allows for flexible driver positioning. Twist lock connector for easy installation. 509506931
- 10' Extension Cord Available
- IC Rated
- Not recommended for use with motion sensors, light sensors, timers or any other external controls
- ETL Listed for Damp Locations (Indoor Use Only)
- 50K Life Hours
- 5 year Limited Warranty



ORDERING INFORMATION

PART #	NOTES
LL51030-6-27K	6"/120v/12w/900lm Del@27K/90CRI ESTAR & T24
LL51071-6-30K	6"/120v/12w/900lm Del@30K/90CRI ESTAR & T24
LL51091-6-40K	6"/120v/12w/900lm Del@40K/90CRI ESTAR & T24
LL51111-6-50K	6"/120v/12w/900lm Del@50K/90CRI ESTAR

LL51070-6-30K,
LL51090-6-40K &
LL51110-6-50K have
had a generational
change to
LL51071-6-30K,
LL51091-6-40K &
LL51111-6-50K.
Specs remain the
same.