

## LL52180-3-40K

## LL52190-3-50K

### LED SLIM RECESSED ROUND 3"

**Construction:** Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included

**Dimensions:** 3.35"D x 0.98"H

See Ordering Section for Performance Notes and Energy Star Certifications.

**Notes/Certifications/Warranty:**

- 120V
- See Ordering Section For Wattage
- Available in 27k/30k/40k/50k.
- Dimmable to 10%: See List of Preferred Dimmers
- 26 inch lead wire between light and external driver allows for flexible driver positioning. Twist lock connector for easy installation. 509506931
- 10' Extension Cord Available
- Not recommended for use with motion sensors, light sensors, timers or any other external controls
- ETL Listed for Damp Locations (Indoor Use Only)
- IC Rated
- See Notes for Energy Star Rating and Title 24 Compliant
- Energy Star Rated
- FCC Compliant
- RoHS Compliant
- 50K Life Hours
- 5 year Limited Warranty



#### Preferred Dimmers

**Legrand:** HLV703PTC

**Leviton:** 06674-002-10W, DSL06-001-1LZ, DW6HD, IPLO06-011-10Z, RDL06-001-1OZ, RNL06-001-10Z, TSL06, DW1KD, DDMX1-BLZ, DSL06-1LZ, C22-6672-1LW, C26-RNL06-TW, R62-6683-1W

**Lutron:** DVCL-153P, DVCL-153PR-WH, MACL153M, PD-6WCL, MRF2-6CL, TGCL153PH-WH-C, SCL-153P, DVCL-253P, CTCL-153PH, CTCL-153P, PD-10NXD

**Pass&Seymour:** H703PTC



#### ORDERING INFORMATION

PART #	NOTES
LL52180-3-40K	3"/120v/7w/450lm Del@40K/80CRI 120° Beam Spread
LL52190-3-50K	3"/120v/7w/450lm Del@50K/80CRI 120° Beam Spread