

## LLS29XXX SERIES-13R

### 13" Round LED Slim Ceiling Light

**Housing:** Aluminum

**Lens:** Glass

**Dimensions:** 13.0" OD x 1.0"H

**Notes:**

- 108° Beam Angle
- Dimmable- See Notes
- Twist and Lock Mounting Bracket
- Mounts Directly to a 3" and 4" Junction Box
- Operating Temperature: -17°C (+1.4°F) to a maximum of +45°C (+113°F)
- See Notes for Energy Star Rating and CA Title 24

**Certifications/Warranty:**

- Damp Location Rated.  
*(\*Dry Location with Emergency Battery Module Installed.)*
- Complies with NEC 410.16 (C) (5)
- cETLus Listed
- RoHS Compliant
- 50K Life Hours
- 5 Year Limited Warranty.



White (WHT)



Brushed Nickel (BN)



Bronze (BRZ)



Black (BLK)



Easy Mount  
Twist and  
Lock Bracket

PART #	NOTES	ACCESSORIES
LLS29650-13R-WHT-30K	120V/25W/90CRI/1500LM@30K/White ESTAR/T24 TRIAC	N/A
LLS29691-13R-WHT-40K	120V/25W/90CRI/1800LM@40K/White ESTAR/T24 TRIAC	
LLS29651-13R-BN-30K	120V/25W/90CRI/1500LM@30K/Brushed Nickel ESTAR/T24 TRIAC	
LLS29652-13R-BRZ-30K	120V/25W/90CRI/1500LM@30K/Bronze ESTAR/T24 TRIAC	
LLS21541-13R-BLK-30K	120V/25W/90CRI/1500LM@30K/Black ESTAR/T24 TRIAC	