

LL1130D-3MCT
LL1132D-3MCT
 12" and 14" Ceiling Fixture in Satin Nickel

Construction:

Body Material: Cold Rolled Steel

Shades:

- LL1130D: Alabaster Glass Diffuser Standard*
- LL1132D: Acrylic Diffuser Standard*

*Other Shades May be Available by Special Order MOQ and longer lead times apply.

Finishes: Brushed Nickel (BN) Standard.

Custom Color (CC) Available by Special Order

Mounting: Ceiling Mount

Dimensions:

LL1130D-3MCT: 12.0"OD x 4.6"H

LL1132D-3MCT: 14.50"OD x 5.4"H

Light Source:

LL1130D-3MCT: 120~277V/18W/3MCT/1280lm/80CRI/Non-Dimming Standard

LL1132D-3MCT: 120~277V/18W/3MCT/1600lm/80CRI/Non-Dimming Standard

- 3MCT: 30K/35K/40K

Dimming: Non-Dimming Standard. TRIAC[^] or 010V offered as Options.

[^]If TRIAC Dimming is selected fixture will be 120V only.


Lumencia recommends the use of a UL or ETL LED Ready Dimmer. Please contact Lumencia for a complete list of compatible dimmers. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects.

EM For LL1132D-3MCT only: Emergency Battery Backup- Provides Battery Backup in the event of a power failure.

BI: For LL1132D-3MCT only: Bi-Level OCS: Occupancy Sensor with Multiple Settings. Hold Time from 5 Seconds to 20 Minutes. Standby dimming 10%-50%.

Certification/Warranty

- ETL/cETL Listed for Damp Locations
- 5 Year Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



ORDERING INFORMATION

Model	Finish	Shade	Options
LL1130D-3MCT	SN(Std) CC*	AB: Alabaster (STD) AC: Acrylic*	010V - 010v Dimming TRIAC[^] - TRIAC Dimming [^] Fixture is 120V Only
LL1132D-3MCT	SN(Std) CC*	AC: Acrylic (STD) AB: Alabaster*	010V - 010v Dimming TRIAC[^] - TRIAC Dimming EM - Emergency Battery Backup BI - BI-Level OCS EM/BI - EM and BI-Level [^] Fixture is 120V Only

*Special Order- MOQ and Longer Lead Times may Apply. May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information.