

Job Name: _____

Type: _____

Part #: _____

Notes: _____

LL2-0245D-A LL2-0246D-A Round Drum Ceiling Fixture

Finish: White (WH)

Lens: White Acrylic

Dimensions:

LL2-0245D: 11.0"OD x 3.3"E

LL2-0246D: 14.0"OD x 3.6"E

Light Source:


- **LL2-0245D-A[^]:** UNV/17w/1600lm Del@30k/80CRI. Non-Dimming Standard
- **LL2-0246D-A:** UNV/24w/2560lm Del@30k/80CRI. Non-Dimming Standard

Options:

- 010V: 010V Dimming
- TRIAC[^]: TRIAC Dimming *Available for LL2-0245D-A Only*
- EM: Emergency 8W of Battery Backup. Requires Deeper Base (adds 1.0" to Height).
- BI: Bi-Level OCS with Multiple Settings. Hold from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%. Requires Deeper Base (Adds 1.0" to Height)

Certification/Warranty:

- ETL/cETL Listed for Damp Locations (Indoor Use Only)
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects
- Energy Star Rated



EM/BI Level Adds 1" to Height

Model	Color Temp.	Finish	Options
LL2-0245D-A LL2-0246D-A	30K 40K MCT*	WH- White	010V- 010V Dimming TRIAC[^]- TRIAC Dimming <small>(*) Only available for LL2-0245D-A only</small> EM- Emergency Battery Backup BI- Bi-Level OCS EM/BI- Combination EM and OCS

*Special Order- MOQ and Longer Lead Times may Apply
 May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information. Specifications are subject to change without Notice.