

# LL3-4082D

## Traditional Exterior Wall Sconce

**Construction:**
**Body Material:** Die-cast Aluminum with Powder Coat Finish

**Lens:** White Polycarbonate

**Finish:** Black (BLK) Standard. Custom Color (CC) By Special Order

**Mounting:** Wall Mount

**Dimensions:** 9.80"H x 7.80"W x 4.20"E

**Light Source:**

- **LL3-4082D:** 120`277VV/16w/850lm Delivered@30K/80CRI/Non-Dimming Standard
- Stocked in 30K and 40K
- 120V TRIAC and 0-10V Dimming Optional

- **LL3-4082D-11W:** 120V/11w/500lm Delivered@30K/80CRI/120V TRIAC Dimming Standard


- **LL3-4082D-JA8:** 120V/15w/680lm Delivered@30K/90CRI/120V TRIAC Dimming Standard

**Dimming:** 120V TRIAC or 010V Dimming. Lumencia recommends the use of a UL or ETL LED Ready Dimmer. Please contact Lumencia for a complete list of compatible dimmers. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects

**Options:** Photocell

**Notes/Certifications/Warranty:**

- UL/cUL, ETL/cETL Listed for Wet Locations
- LL3-4082D-JA8: CEC Listed, Meets Title24 JA8 Requirements
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



Model	Color Temp.	Finish	Options
LL3-4082D LL3-4082D-11W	30K 40K	BLK CC*	PC: Photocell* TRIAC: TRIAC Dimming^ 010V: 010 Dimming^
LL3-04082D-JA8-30K			^Dimming for LL3-4082D only

\*Special Order-MOQ and Longer Lead Times may Apply.  
May be available with other voltage, wattage, and finish options by special order.  
Please contact your Lumencia Representative for more information