



Job Name: _____
Type: _____
Part #: _____
Notes: _____

LL4325D2-12R-LED

LL4326D2-14R-LED

LL4327D2-16R-LED

Brushed Nickel LED Flush Ceiling or Wall Mount
in 3 Sizes.



Construction:

Housing: Hard Gauge Metal Backplate and Heat Sink

Lens: Frosted White Polycarbonate

Finishes: Brushed Nickel (BN) Standard, Custom Color (CC) By Special Order.

Mounting: Ceiling or Wall Mount

Dimensions:

LL4325D2-12R-LED: 12.81"OD X 3.81"H

LL4326D2-14R-LED: 13.81"OD X 3.81"H

LL4327D2-16R-LED: 15.81"OD X 4.44"H

Light Source:

LL4325D2-12R-LED: 120V/15.1W/1309lm(Source)/982lm Del@30K/80CRI/Dimmable

LL4326D2-14R-LED: 120V/ 21.3W/1684lm(Source)/1263lm Del@30K/80CRI/Dimmable

LL4327D2-16R-LED: 120V/34W/2185lm(Source)/1639lm Del@30K/80CRI/Dimmable

Dimming: TRIAC/ELV Dimming 10-100%. Lumencia recommends the use of a UL or ETL LED Ready Dimmer. Please contact Lumencia for a complete list of compatible dimmers. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects.

Option: Emergency 9W Battery Back Up Available (BBU)

Notes/Certifications/Warranty:

- 120V
- cCASus Listed for Damp Locations
- 50K Life Hours
- LED Light Source: 5 Year Limited Warranty
- Non-Electrical: 1 Year Limited Warranty



| PART # | FINISH | OPTIONS |
|--|-----------|---------|
| LL4325D2-12R-LED LL4326D2-14R-LED LL4327D2-16R-LED | BN CC* | BBU |