

## DISCONTINUED 01/13/2023

### LL519XX SERIES

6" LED RECESSED SLIM SQUARE

**Construction:**

- Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included

**Dimensions:** 6.72"SQ x 0.98"H

**See Ordering Section for Performance Notes and Energy Star/T24 Certifications.**

**Notes/Certifications/Warranty:**

- 120V
- 12w
- Available in 27K/30K/40K/50K.
- 120° Beam Spread
- Dimmable to 10%. Recommended Dimmers
  - **Leviton:** CD-C22-06672-12A, CD-R00-RNL06-12
  - **Lutron:** CTCL-153P-WH, DVCL-153P, DVCL-153PR-WH, DVCL253P-WH, LGCL-153PLH, MACL-153M-WH, MACL-153PLH-WH, MRF2-6CL-WH, PD-10NXD-WH, PD-6WCL-WH, S-600P-WH, S603PG, SCL-153P, TGCL-153P
- Not recommended for use with motion sensors, light sensors, timers or any other external controls
- 26 inch lead wire between light and external driver allows for flexible driver positioning.
- Twist lock connector for easy installation. 509506931
- 10' Extension Cord Available
- IC Rated
- ETL Listed for Damp Locations (Indoor Use Only)
- 50K Life Hours
- 5 year Limited Warranty



**ORDERING INFORMATION**

PART #	NOTES
LL51900-6-27K	6"/120v/12w/900lm Del@27K/90CRI ESTAR & T24
LL51910-6-30K	6"/120v/12w/900lm Del@ 30K/90CRI ESTAR & T24
LL51920-6-40K	6"/120v/12w/900lmDel@40K/90CRI ESTAR & T24
LL51930-6-50K	6"/120v/12w/900lm Del@50K/90CRI ESTAR