

LL52-1059-MBLED

52" Ceiling Fan with. Medium Base LED Light Kit in 3 Finishes

Construction:

Body Materials: Silicon steel, steel, copper, aron, aluminum alloy, zinc alloy, plastic.

Lens: Frosted glass

Blades: 5 MDF blades

Finishes:

- **BNW:** Brushed Nickel body with reversible Silver and Walnut blades.
- **MBK:** Matte Black body with reversible Matte Black and Walnut blades.
- **MWH:** Alabaster White body with reversible Matte White and Gray Oak blades.

Dual Mount: Close to ceiling or down rod compatible - comes with 4" down rod.

For flat ceiling only – sloped ceilings require the LLDRSA45 adapter for ceilings with up to a 45° slope.

Dimensions: 52.00"D × 18.00"E with included down rod.

- Includes 52" of lead wire.

Light Source: Includes 2 X 120V/9W(18W total)/1600lm(source)/1042lm (Del)/30K/80CRI/Dimmable medium base A19 LED lamps.

Dimming: Lumencia recommends the use of a UL or ETL LED ready dimmer that is compatible with your chosen lamps. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects.

Notes/Certifications/Warranty:

- 120V
- Pull chain standard.
- Controls - see page 2.AC Motor: 153 × 12mm
- Speed: 3; reversible
- **RPM:** Low: 68 RPM / High: 160 RPM
- **CFM:** Low: 1,868.07 CFM / High: 4,337.85 CFM
- UL listed for dry locations
- CEC Compliant; Title 20
- Fan motor has a limited lifetime warranty
- 1 year limited warranty on all other components



ORDERING INFORMATION

Model	Finish
LL52-1059-MBLED	BNW MBK MWH

Down Rods

LLDR 1/2" Down rods available in several sizes.

Features.

- 0.5" Diameter Down rod
- Available in 12", 18", 24", 36", 48", 60", and 72"
- Recommended 7' of clearance under ceiling fan blades



Part #	Finish
LLDR12	BN
LLDR18	MWH
LLDR24	MBK
LLDR36	
LLDR48	
LLDR60	
LLDR72	

Part #	Image	Speeds/ Light Control	Electrical Notes	Notes
LLRC-10-AC 3 Speed Hand-held remote control for AC motor ceiling fans		• 3-speed fan control - Hi, Med, Low, Off • Light control - On-Off, full-range dimming	• 120V/ 60Hz • 3-wire installation • 1.5A Max Load for Ceiling Fan • 300W Max Load for Light • Compatible with LED, CFL and Incandescent Fans Transmitter: Requires 9V Battery (not included) Receiver: 4-DIP Switches; 16 possible combination for multiple fan operation Not Suitable for Multi-Family Units	Dimensions: 4.5" L x 4.5" W x 0.87" W • Canopy Wall Mount • White Finish • 3 Wire Installation • Use with CFL and LED Source • Maximum distance is 20 feet • UL Listed for Dry location applications • FCC Certified • 1 Year Limited Warranty 
LLWC8-WH 4 Speed Wall Control for Fans with Light Kits		• 4 Speed Fan Control • Full-range dimming of light	• 120V/ 60Hz • 3-wire installation • Compatible with LED, CFL and Incandescent Fans	Dimensions: 1.75"W x 4.125"H1.75"W x 4.125"H • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations 
LLWC16-WH 3 Speed Wall Control for Fans with Light Kits		• 3 Speed Fan Control- Hi, Med, Low, Off • On/Off Light Control	• 120V/ 60Hz • 3-wire installation • Compatible with LED, CFL and Incandescent Fans	Dimensions: 1.75"W x 4.125"H1.75"W x 4.125"H • Installs in a standard single-gang electrical box. • Wall Control must be Mounted Indoors • Not for Multiple Fan Control • cULus Listed for Dry Locations 