

LL52-1067-ES 52" Energy Star Ceiling Fan. Wet Location Rated.

Finishes:


- Brushed Pewter with Brushed Pewter Blades (BP)
- Matte Black with Matte Black Blades (MBL)
- Oil Rubbed Bronze with Oil Rubbed Bronze Blades (ORB)
- White with White Blades (WH)

Dimensions: 52"OD x 12.375"OH

Blades: 3 Blades.

Notes/Certifications/Warranty:

- 120V
- 4" Downrod
- Downrod Mount Only
- Lead Wire: 76"
- Pull Chain Standard
- Remote Control *(Sold Separately Part# LLRC-10-AC For Indoor Use Only)*
- Wall Control *(Sold Separately Part# LLWC-8 or LLWC-16 For Indoor Mounting Only)*
- *Light Kit (Sold Separately Part# LL1RP69LK-LED)*
- AC Motor | 172 x 14 mm motor | 3 capacitors
- Speeds: 3, Reversible
- RPM: 209 (High)/83 (Low)
- CFM: 5600
- Airflow Efficiency: 110
- ETLus Listed for Wet Locations
- CEC Title 20 Compliant
- Energy Star Rated
- Limited Lifetime Motor Warranty
- All other Parts Have a 1 Year Warranty.



ORDERING INFORMATION

Model	Finish
LL52-1067-ES	BP ORB MBL WH

LL1RP69LK-LED Light Kit

Wet Location Rated Light Kit. Available in 4 Finishes

Finishes:

- Brushed Pewter (BP)
- Matte Black (MBL)
- Oil Rubbed Bronze (ORB)
- White (WH)

Lens: Acrylic

Light Source: 120V/12W/700 lms Del@30K/90 CRI/Dimmable

Notes/Certifications/Warranty:

- 120V
- Pull Chain Standard
- Compatible Fans: LL52-1067 Series
- Remote Control: Adaptable (Sold Separately Part# LLRC-10)
- Wall Control Adaptable (Sold Separately Part# WC-8 | WC-16)
- ETLus Listed for Wet Locations
- CEC JA8 Compliant
- Energy Star Rated
- LED Light: 5 Year Limited Warranty
- 50 Life Hours
- Non-Electrical: 1 Year Limited Warranty



ORDERING INFORMATION

Model	Finish
LL1RP69LK-LED	BP MBL ORB WH

Wireless Remote With Receiver

LLRC-10-AC 3 Speed Remote Control

Features:

- Hand-held remote control for AC motor ceiling fans
- 3-speed fan control - Hi, Med, Low, Off
- Light control - On-Off, full-range dimming
- Canopy Wall Mount
- White finish

Dimensions: 4.5" L x 4.5" W x 0.87" W

Electrical:

- 120V/ 50-60 H
- 3 Wire Installatio
- 1.5A Max Load for Ceiling Fa
- 300W Max Load for Ligh
- Use with CFL and LED Source
- Maximum distance is 20 fee

Transmitter:

- Listed for Dry location applications onl
- Requires 9V Battery (not included)

Receiver:

- 4-DIP Switches; 16 possible combination fo multiple fan operation
- Not Suitable for Multi-Family Units



Notes/Certifications/Warranty:

- UL Listed for Dry Location
- FCC Certified
- 1 Year Limited Warranty



ORDERING INFORMATION

Model
LLRC-10-AC



Remote control transmitter wall mounted holder

Wall Controls

LLWC8-WH 4 Speed

Features:

- 4 Speed Fan Control
- Full-range dimming of light


Dimensions: 1.75"W x 4.125"H

Electrical:

- 120V/ 60Hz
- 3-wire installation
- Compatible with LED, CFL and Incandescent

Notes/Certifications/Warranty:

- Installs in a standard single-gang electrical box.
- Not for Multiple Fan Control
- cULus Listed



LLWC-16WH 3 Speed

Features:

- Single sliding 3-speed on/off control switch for ceiling fans; High, Medium, Low, Off
- On/Off Light Control

Dimensions: 1.77" W x 4.134" H x 1.97" D

Electrical:

- 120V/ 60Hz
- 3-wire installation
- Compatible with LED, CFL and Incandescent

Notes/Certifications/Warranty:

- Installs in a standard single-gang electrical box.
- Not for Multiple Fan Control
- cULus Listed



ORDERING INFORMATION

Model
LLWC8-WH LLWC-16WH