Lumencia
Multi-Unit Residential Lighting

Job Name:

Type:

Part #:

Notes:

LL52-72XXX-LED Series

52” LED Ceiling Fan in 3 Finishes with Integrated Dimmable LED light.

Finishes: See Ordering Section Below

Shade: Frosted Glass

Blades: 5 Reversible Plywood Blades

Dimensions: 52"OD x 14.3"H*

Light Fixture: Integrated LED 120V/16W/16850lm Del@30K/80CRI - Dimming Standard

LL52-72242MBL-LED

LL52-72336WHT-LED

LL52-72341BPW-LED

Notes:

- Down Rod (included): 0.75" x 4"
- Lead Wire: 78"
- Installation: Dual
- Remote Control Adaptable
- Silcon Steel Motor 153mm
- Speeds: 3 Forward, 1 Reverse.
- Airflow(CFM): 4460 w/down rod/3589 w/out down rod
- Airflow Efficiency(CFM/W): 82 w/down rod/ 64 w/out down rod
- RPM(High): 147
- Amp(High): 0.52
- Watts(High): 63

Warranty/Certifications:

- 25K Life Hours
- Limited Lifetime motor warranty.
- All other Parts have a 2 Year Warranty.
- cETLus Listed for Dry Location Rated

Intertek

ORDERING INFORMATION

Part #	Notes
LL52-72242MBL-LED	Matte Black Finish w/ Matte Black/Marble Blades
LL52-72336WHT-LED	White Finish w/ White/White Washed Pine Blades
LL52-72341BPW-LED	Brushed Pewter Finish w/ Maple/White Blades

*If a Combo Style Fan with a 4" Down Rod is installed without the Down Rod, Subtract 3" from the Dimensions Listed (A, B, F).
If a Combo Style Fan with a 6" Down Rod is installed without the Down Rod, Subtract 5" from the Dimensions Listed (A, B, F).

LL52-73054BN-C-LED & LL52-7305WHR-C-LED
Candelabra Based Versions on Second Page

2022.04

Phone: 215-512-7000 **Fax:** 267-288-5604
www.Lumencia.com

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED

Lumencia
Multi-Unit Residential Lighting

Job Name:

Type:

Part #:

Notes:

LL52-73054BN-C-LED
LL52-73055WHR-C-LED
52” Ceiling Fan in 2 Finishes with Dimmable Candelabra Base LED Lamps

LL52-73054BN-C-LED

LL52-73055WHR-C-LED

Finishes: See Ordering Section Below

Shade: Frosted Glass

Blades: 5 Reversible Plywood Blades

Dimensions: 52"OD x 14.3"H*

Light Fixture: Includes 2 x E12 Candelabra Base Lamps 4.5w/250lm 30K/80CRI- Dimmable

Notes:

- Down Rod (included): 0.75" x 4"
- Lead Wire: 78"
- Installation: Dual
- Remote Control Adaptable
- Silcon Steel Motor 153mm
- Speeds: 3 Forward, 1 Reverse.
- Airflow(CFM): 4460 w/down rod/3589 w/out down rod
- Airflow Efficiency(CFM/W): 82 w/down rod/ 64 w/out down rod
- RPM(High): 147
- Amp(High): 0.53
- Watts(High): 63

Warranty/Certifications:

- 15K Life Hours
- Limited Lifetime motor warranty.
- All other Parts have a 2 Year Warranty.
- cETLus Listed for Dry Location Rated

Intertek

ORDERING INFORMATION

Part #	Notes
LL52-73054BN-C-LED LL52-73055WHR-C-LED	Brushed Nickel Finish w/ Charcoal/Wengue Blades White Finish w/ Rustic Birch/Graphite Blades

*If a Combo Style Fan with a 4" Down Rod is installed without the Down Rod, Subtract 3" from the Dimensions Listed (A, B, F).
If a Combo Style Fan with a 6" Down Rod is installed without the Down Rod, Subtract 5" from the Dimensions Listed (A, B, F).

2022.04

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED