

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

## LL52140-4-27K-GR LL52150-4-30K-GR 12 Watt 4" Gimbal Recessed LED Downlight

**Housing/Finish:** Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included.

**Dimensions:**

- **LL52140-4-27K-GR:** 5.04"OD x 2.24"L
- **LL52150-4-30K-GR:** 5.04"OD x 2.24"L

**Light Source:**

- **LL52140-4-27K-GR:** 120V/12W/850lm Delivered@27k/90CRI.
- **LL52150-4-30K-GR:** 120V/12W/850lm Delivered@30k/90CRI.



**Notes:**

- Gimbal ring rotates 360 degrees and angles up to 30 degrees
- 40° Beam Spread
- Includes 26" of Feed Wire Between Light and External Driver

Provides Flexible Driver Positioning

- Fully Dimmable- Instant on: Compatible with most Dimmers
  - o **Leviton:** 6631, 6633-P, 6672, 6674
  - o **Lutron:** CTCL-153P, MACL-153M, DVCL-153P, LGCL-153P, TGCL-153P, SCL-153P, S-600, S-600P, DVCLV-300P, CT-103P, DV-600P, S2-L, TG-600P
  - o **Cooper:** DIO6P

**Warranty:**

- 5 Year Limited Warranty
- 50K Life Hours
- cETLus Rated
- Damp Location Rated (Indoor Use Only)
- RoHS Compliant
- Energy Star Rated
- IC Rated
- Can be used to comply with the 2019 Title 24, Part 6 high efficacy light source requirements in the state of California.



<b>MODEL</b>
LL52140-4-27K-GR LL52150-4-30K-GR

**Not recommended for use with motion sensors, light sensors, timers or any other external controls.**  
May be available with other voltage, wattage, finish, and cable length options by special order.  
Please contact your Lumencia Representative for more information