

LL52260-4-MCT-BFL LL52270-6-MCT-BFL

Slim Recessed LED Step-Baffle Downlight with Color Temperature Selection.

Available in 2 sizes.

Housing/Finish: Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included.

Dimensions:

- **LL52260-4-MCT-BFL:** 5.04"OD x 1.42"L
- **LL52270-6-MCT-BFL:** 7.17"OD x 1.42"L

Light Source:

- **LL52260-4-MCT-BFL:** 120V/10W/650lm Delivered@30k/90CRI.
- **LL52270-6-MCT-BFL:** 120V/12W/900lm Delivered@30k/90CRI.

Notes:

- MCT - Selectable CCT 27K, 30K, 35K, 40K, 50K
- 110° Beam Spread
- Includes a 13" Driver Connect for Flexible Mounting.
- Rough in Brackets Available
 - o LL509506913-4 for LL52260-4-MCT-BFL: 6.25"L x 26"W x 0.0625"E
 - o LL510306913-6 for LL52270-6-MCT-BFL: 8.375"L x 26"W x 0.0625"E
- Fully Dimmable- Instant on: Compatible with most Dimmers
 - o **Leviton:** 011-IPL06-10Z, 012-TSL06-1LW, 001-RDL06-10Z, 1-RNL06-10Z, 002-6674-10W, 001-DW6HD-1BZ, 001-DW1KD-1BZ, 001-DSL06-1LZ, R62-06674-POW, R12-06672-1LW
 - o **Lutron:** DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WWH-R
 - o **Eaton:** SAL06-LA-K



LL52260-4-MCT-BFL



LL52270-6-MCT-BFL

Warranty:

- 5 Year Limited Warranty
- 50K Life Hours
- cETLus Rated
- IP40 for Wet Locations
- RoHS Compliant
- Energy Star Rated
- Title 24 Can be used to comply with the 2019 Title 24, Part 6 High Efficacy Light Source Requirements.
- IC Rated



MODEL	ROUGH IN BRACKETS (ORDER SEPARATELY)
LL52260-4-MCT-BFL LL52270-6-MCT-BFL	LL509506913-4 LL510306913-6

Not recommended for use with motion sensors, light sensors, timers or any other external controls.
May be available with other voltage, wattage, finish, and cable length options by special order. Please contact your Lumencia Representative for more information