

# LL52370-4-MCT-DBFL LL52380-6-MCT-DBFL

## Deep-Baffle LED Downlight with Color Temperature Selection.

Available in 2 sizes.

**Housing/Finish:** Aluminum Construction with White Finish and Frosted Polycarbonate Lens. Junction Box and Driver Connect Included.

**Dimensions:**

- **LL52370-4-MCT-DBFL:** 1.75"H x 5.06" OD. 3.125" Aperture
- **LL52380-6-MCT-DBFL:** 1.875"H x 7.06" OD. 3.125" Aperture

**Light Source:**

- **LL52370-4-MCT-DBFL:** 120V/12W/750lm Delivered@30k/90CRI.
- **LL52380-6-MCT-DBFL:** 120V/15W/1000lm Delivered@30k/90CRI.

**Notes:**

- MCT - Selectable CCT 27K, 30K, 35K, 40K,50K
- 100° Beam Spread
- Includes a 13" Driver Connect for Flexible Mounting.
- Rough in Brackets Available
  - o LL509506913-4 for LL52370-4-MCT-DBFL: 6.25"L x 26"W x 0.0625"E
  - o LL510306913-6 for LL52380-6-MCT-DBFL: 8.375"L x 26"W x 0.0625"E
- Fully Dimmable- Instant on: Compatible with most Dimmers
  - o **Leviton:** 011-IPL06-10Z, 012-TSL06-1LW, 001-RDL06-10Z, 001-RNL06-10Z, 2-6674-10W, 001-DW6HD-1BZ, 001-DW1KD-1BZ, 001-DSL06-1LZ
  - o **Lutron:** DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R, R62-06674-P0W, R12-06672-1LW, R50-1PL06-10M
  - o **Eaton:** SAL06-LA-K



LL52370-4-MCT-BFL



LL52380-6-MCT-BFL

**Warranty:**

- 5 Year Limited Warranty
- 50K Life Hours
- cETLus Rated
- IP40 for Wet Locations
- RoHS Compliant
- Energy Star Rated
- Title 24 Can be used to comply with the 2019 Title 24, Part 6 High Efficacy Light Source Requirements.
- IC Rated



MODEL	ROUGH IN BRACKETS <i>(ORDER SEPARATELY)</i>
LL52370-4-MCT-DBFL LL52380-6-MCT-DBFL	LL509506913-4 LL510306913-6

**Not recommended for use with motion sensors, light sensors, timers or any other external controls.**  
May be available with other voltage, wattage, finish, and cable length options by special order. Please contact your Lumencia Representative for more information