

LL62-114XR1-LED Series

2 Light Up and Down Wall Cylinder in 3 Finishes and Sizes.

Construction: Powder coated Die-Cast Aluminum with Glass Lens.

See Ordering Section For Performance, Dimensions and Colors

Notes/Warranty/Certifications:

- Non Dimming
- Up/Down Mounting
- 2kv Surge Protection
- 40° beam Spread
- -30C (-22F) to a maximum of +50C (+122F)
- IP65
- cETLus Rate For Wet Locations.
- Energy Star Rated
- RoHS
- Title 24 Compliant
- 5 Year Limited Warranty
- 5K Life Hours



LL62-1141R1-WHT-LED



LL62-1142R1-BLK-LED



LL62-1145R1-BR-LED

Dimensions : 5" W x 6 3/4" H x 3 3/8" Ext.



LL62-1143R1-WHT-LED



LL62-1144R1-BLK-LED



LL62-1146R1-BR-LED

Dimensions : 5" W x 11 3/4" H x 4 1/8" Ext.

ORDERING INFORMATION

PART #	NOTES
LL62-1141R1-WHT-LED	White Finish: UNV/10W/900lms Del@30K/90CRI 5.00"W x 6.75"H x 3.41"E
LL62-1142R1-BLK-LED	Black Finish: UNV/10W/900lms Del@30K/90CRI 5.00"W x 6.75"H x 3.38"E
LL62-1145R1-BR-LED	Bronze Finish: UNV/10W/900lms Del@30K/90CRI 5.00"W x 6.75"H x 3.41"E
LL62-1143R1-WHT-LED	White Finish: UNV/20W/1800lms Del@30K/90CRI 5.00"W x 11.75"H x 4.125"E
LL62 1144R1 BLK LED	Black Finish: UNV/20W/1800lms Del@30K/90CRI 5.00"W x 11.75"H x 4.125"E
LL62-1146R1-BR-LED	Bronze Finish: UNV/20W/1800lms Del@30K/90CRI 5.00"W x 11.75"H x 4.125"E