

LL65-108X & LL65-109X

2' and 4' LED Wrap in 30K or 40K with
Optional Pull-chain or Motion Sensor

Finish and Lens: White Powder Coat with Opaque
Acrylic Lens

Dimensions:

- 4': 47.41"L x 5.5"W x 2.59"H
- 2': 24.45"L x 5.5"W x 2.59"H

See Ordering Section For Performance

Motion Sensor: Recommended for mounting at
7'-13'. Detection distance 13'-20'. On-Off Only -
Shuts off after 50 seconds of no detection.

Notes/Certifications/Warranty:

- Pull Chain Option is 30K and 120v Only.
- Complies with NEC410.16 (C)(5) for use in closets.
- ETL Rated For Damp Locations
- RoHS Compliant
- 50K Life Hours
- 5 Year Limited Warranty on LED
- 1 Year Limited Warranty on Body and Lens



PART #	NOTES
LL65-1081-2-UNV-40K	2'- 120-277V/20W/1600lms Del@40K/90CRI
LL65-1083-2-UNV-30K	2'- 120-277V/20W/1600lms Del@30K/90CRI
LL65-1091-2-30K-PC	2' with Pullchain- 120V/20W/1600lms Del@30K/90CRI
LL65-1095-2-UNV-30K-MS	2' with Motion Sensor- 120~277V/20W/1600lms Del@30K/90CRI
LL65-1097-2-UNV-40K-MS	2' with Motion Sensor- 120~277V/20W/1600lms Del@40K/90CRI
LL65-1082-4-UNV-40K	4'- 120~277V/40W/3200lms Del@40K/90CRI
LL65-1084-4-UNV-30K	4'- 120~277V/40W/3200lms Del@30K/90CRI
LL65-1092-4-30K-PC	4' with Pullchain- 120V/40W/3200lms Del@30K/90CRI
LL65-1096-4-UNV-30K-MS	4' with Motion Sensor- 120~277V/40W/3200lms Del@30K/90CRI
LL65-1098-4-UNV-40K-MS	4' with Motion Sensor- 120~277V/40W/3200lms Del@40K/90CRI