

LL65-121X Series

2' and 4' Ceiling Wrap in White. Standard, Pull Chain, and Motion Sensor Models.

Materials:

Body: Steel

Shade: Polycarbonate

See Ordering Notes for Dimensions and Performance

Notes/Certifications/Warranty:

• **Voltage:**

◦ Standard and MS Models: (UNV): 120~277V

◦ Pull Chain Model: 120V

• **Selectable Color Temp:** 5MCT-27K/30K/35K/40K/50K

• cETLus Listed for Damp Locations

• FCC Compliant

• RoHS Compliant

• Complies with NEC 410.16 (A)(3)& NEC 410.16 (C)(5)

• 50K Life Hours

• 5 Year Limited Warranty



Mounting: Maybe Installed On Wall or Ceiling

LL65-1214-2-LED-5MCT-MS / LL65-1215-4- LED-5MCT-MS:

Motion Sensor Specifications:

• PIR type (passive infrared sensor)

• Max Installation: 3m / 9.84'

• Detection Distance: 2.5m / 8.2'

• No Detection Shut Off Time: 5 Minutes



PART #	NOTES
LL65-1210-2-LED-5MCT	24.33"L x 5.50"W x 2.56"H 120~277V/20W/1650lm(Max)/90CRI/Non-Dimming
LL65-1211-4-LED-5MCT	47.24"L x 5.50"W x 2.56"H 120~277V/39W/3400lm(Max)/90CRI/Non-Dimming
LL65-1212-2-LED-5MCT-PCH	24.77" x 5.50"W x 2.56"H 120V/20W/1650lm(Max)/90CRI/Non-Dimming
LL65-1213-4-LED-5MCT-PCH	47.68" x 5.50"W x 2.56"H 120V/39W/3400lm(Max)/90CRI/Non-Dimming
LL65-1214-2-LED-5MCT-MS	24.33" x 5.50"W x 2.56"H 120~277V/20W/1650lm(Max)/90CRI/Non-Dimming
LL65-1215-4- LED-5MCT-MS	47.24" x 5.50"W x 2.56"H 120~277V/39W/3400lm(Max)/90CRI/Non-Dimming