

**LL65-747-LED**  
**LL65-748-LED**  
**LL65-748-LED**

Small Wall Pack with Photocell Selectable Color Temperature. Available in 3 Finishes.

**See Notes for Finishes**

**Construction:** Cast Aluminum with Polycarbonate Lens

**Dimensions:** 8.6"H x 5.8"W x 3.1"E

**Light Source:** UNV/20W/80CRI/Dimmable

**Lumen Output:** 2608.9lm/30K, 2920.8lm/40K, 2703.4lm/50K

**Notes/Certifications/Warranty:**

- UNV= Universal Voltage, 120~277V
- 0-10V Dimming
- Has Photocell
- Beam Angle: 100
- Surge Protection: 2.5KV
- Operating Temperature: -20°C (-4°F) to a maximum of +45°C (+113°F)
- cULus Listed for Wet :Locations
- ADA Compliant
- California T24 Compliant
- IP65
- RoHS Compliant
- FCC Compliant
- 50K Life Hours
- 5 Year Limited Warranty



**ORDERING INFORMATION**

Model	Notes
LL65-747-LED	Y æ  ÁÚæ&\Áä } ÁÓ æ&\
LL65-748-UÜÓĒLED	Y æ  ÁÚæ&\Áä } ÁUá ÁÜ ~ ää^ääÓ! [ ] : ^
LL65-748-Y PĒLED	Y æ  ÁÚæ&\Áä } Á Y @äc^