



Job Name: _____

Type: _____

Part #: _____

Notes: _____

LL8530-X-30K-WHT

LL8530-X-5MCT-WHT

Surface Downlight in 4 Sizes.

Available in 30K or 5MCT.



Construction:

Body Material: Steel and Aluminum

Lens: Polycarbonate

Finish: White (WHT)

Mounting: Ceiling surface downlight.

Part #	Dimensions	Performance
LL8530-6-X-WHT	6.25"OD x 1.00"E	120V/8W/840(Source)/700lmDEL@30K/90CRI/Dimmable
LL8530-7.5-X-WHT	7.50"OD x 1.25"E	120V/14W/1503(Source)/1200lmDEL@30K/90CRI/Dimmable
LL8530-9-X-WHT	9.00"OD x 1.50"E	120V/17W/1573(Source)/1300lmDEL@30K/90CRI/Dimmable
LL8530-13-X-WHT	13.00"OD x 1.75"E	120V/24W/2164(Source)/1800lmDEL@30K/90CRI/Dimmable

- **5MCT:** Selectable Color Temperatures 27K/30K/35K/40K/50K

Dimming: TRIAC/ELV Dimming. *Lumencia recommends the use of a UL or ETL LED ready dimmer. Please contact Lumencia for a complete list of compatible dimmers. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects*

Notes/Certifications/Warranty:

- 120V
- ETL listed for wet locations (*covered patio only when used in exterior applications*).
- CEC Compliant
- FCC Compliant
- Title 24 Compliant
- 50K life hours *based on 3 hours of use per day*.
- 5 year limited warranty.



Ordering Information

PART #	SIZE	COLOR TEMPERATURE	FINISH
LL8530	6 7.5 9 13	30K 5MCT	WHT