

LL8532-X-30K-WHT

LL8532-X-5MCT-WHT

Surface downlight in 4 Sizes. Available in 30K or 5MCT.
7" available with emergency battery backup.

Construction:

Body Material: Steel and Aluminum

Lens: Polycarbonate

Finish: White (WHT)

Mounting: Ceiling surface downlight.

Part #	Dimensions	Performance
LL8532-6-X-WHT	5.75"OD x 0.75"E	120V/11W/1000(Source)/700lmDEL@30K/90CRI/Dimmable
LL8532-7-X-WHT	7.00"OD x 0.75"E	120V/16W/1400(Source)/1000lmDEL@30K/90CRI/Dimmable
LL8532-7-X-WHT-EM	7.00"OD x 1.75"H	120V/17W/1400(Source)/1000lmDEL@30K/90CRI/Dimmable
LL8532-11-X-WHT	11.00"OD x 0.75"E	120V/18W/2100(Source)/1400lmDEL@30K/90CRI/Dimmable
LL8532-16-30K-WHT*	16.00"OD x 0.75"E	120V/32W/3400(Source)/2400lmDEL@30K/90CRI/Dimmable

• 5MCT: Color Selectable 27K/30K/35K/40K/50K

* LL8532-16 Not Available in 5MCT Version

LL8532-7-X-WHT-EM: 4W emergency battery backup provides 90 minutes of emergency power.

Dimming: TRIAC/ELV Dimming. Lumencia recommends the use of a UL or ETL LED ready dimmer. Please contact Lumencia for a complete list of compatible dimmers. Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. We recommend testing dimmers prior to installation for larger projects.

Notes/Certifications/Warranty:

- 120V
- ETL listed for wet locations (covered patio only when used in exterior applications).
 - EM is damp location only.
- EM will not work with external controls.
- CEC compliant
- FCC compliant
- Title 24 compliant
- 50K life hours based on 3 hours of use per day.
- 5 Year limited warranty.



LL8532-7-X-WHT-EM

Ordering Information

PART #	SIZE	COLOR TEMPERATURE	FINISH
LL8532	6 7 11 16*	30K 5MCT*	WHT
LL8532-7-30K-WHT-EM LL8532-7-5MCT-WHT-EM			

* LL8532-16-30K-WHT Not Available in 5MCT Version