

LLC11XXD-LED LLC11XXD-P-LED

Modern Ceiling Fixture in Three Sizes.
Available in a Pendant Style with Aircraft Cables.

Finish: Oil Rubbed Bronze (ORB) Standard. Available
by Special Order: Gray (GRY)

Shade: Acrylic

Dimensions:

- **LLC1112D-LED:** 11.80"OD x 2.80"H
- **LLC1116D-LED:** 15.80"OD x 2.80"H
- **LLC1120D-LED:** 19.70"OD x 2.80"H
- **LLC1112D-P-LED:** 11.80"OD x 2.80"H1 x 6'H
- **LLC1116D-P-LED:** 15.80"OD x 2.80"H1 x 6'H
- **LLC1120D-P-LED:** 19.70"OD x 2.80"H1 x 6'H
- Adjustable Aircraft Cable for Pendant Mount Adds Up To 6'

Light Source:

- **LLC1112D-LED/LLC1112D-P-LED:** UNV/21W/1260lm
Del@30k/80CRI. 010V Dimming Standard
- **LLC1116D-LED/LLC1116D-P-LED:** UNV/34W/1980lm
Del@30k/80CRI. 010V Dimming
- **LLC1120D-LED/LLC1120D-P-LED:** UNV/44W/2330lm
Del@30k/80CRI. 010V Dimming Standard

Notes/Certifications/Warranty:

- EM: Emergency Battery Backup. Provides Battery Backup in the event of a power failure.
- BI: Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%
(Only Available for LLC1120D)

- Energy Star Rated
- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



ORDERING INFORMATION

Model	Color Temp	Finish	Options
LLC1112D-LED LLC1116D-LED LLC1120D-LED LLC1112D-P-LED LLC1116D-P-LED LLC1120D-P-LED	30K(Std) 40K* MCT*	ORB(Std) GRY*	EM: Emergency Battery Backup BI: Bi-Level OCS EM/BI: EM and Bi-Level

*Special Order- MOQ and Longer Lead Times may Apply
May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information. Note: Specifications are subject to change without notice.

