



Job Name: \_\_\_\_\_  
Type: \_\_\_\_\_  
Part #: \_\_\_\_\_  
Notes: \_\_\_\_\_

## LLC11XXD-LED LLC11XXD-P-LED

Modern Ceiling Fixture in Three Sizes.  
Available in a Pendant Style with Aircraft Cables.

**Finish:** Oil Rubbed Bronze (ORB) Standard. Available by Special Order: Gray (GRY)

**Shade:** Acrylic

### Dimensions:

- **LLC1112D-LED:** 11.80"OD x 2.80"H
- **LLC1116D-LED:** 15.80"OD x 2.80"H
- **LLC1120D-LED:** 19.70"OD x 2.80"H
- **LLC1112D-P-LED:** 11.80"OD x 2.80"H1 x 6'H
- **LLC1116D-P-LED:** 15.80"OD x 2.80"H1 x 6'H
- **LLC1120D-P-LED:** 19.70"OD x 2.80"H1 x 6'H
- Adjustable Aircraft Cable for Pendant Mount Adds Up To 6'



### Light Source:

- **LLC1112D-LED/LLC1112D-P-LED:** UNV/21W/1260lm  
Del@30k/80CRI. 010V Dimming Standard
- **LLC1116D-LED/LLC1116D-P-LED:** UNV/34W/1980lm  
Del@30k/80CRI. 010V Dimming
- **LLC1120D-LED/LLC1120D-P-LED:** UNV/44W/2330lm  
Del@30k/80CRI. 010V Dimming Standard

### Notes/Certifications/Warranty:

- **EM:** Emergency Battery Backup. Provides Battery Backup in the event of a power failure.
- **BI:** Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%  
(Only Available for LLC1120D)
- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



### ORDERING INFORMATION

Model	Color Temp	Finish	Options
LLC1112D-LED	30K(Std)	ORB(Std)	<b>EM:</b> Emergency Battery Backup
LLC1116D-LED	40K*	GRY*	<b>BI:</b> Bi-Level OCS
LLC1120D-LED	MCT*		<b>EM/BI:</b> EM and BI-Level
LLC1112D-P-LED			
LLC1116D-P-LED			
LLC1120D-P-LED			

\*Special Order- MOQ and Longer Lead Times may Apply  
May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information. Note: Specifications are subject to change without notice.