

Job Name: _____

Type: _____

Part #: _____

Notes: _____

LLC1112D LLC1116D LLC1120D

**Modern Ceiling Fixture in Three Sizes-
Pendant Kit Optional.**

Finish: Oil Rubbed Bronze (ORB) Standard.
Available by Special Order: Gray (GRY)

Shade: Acrylic

Dimensions:

- **LLC1112D:** 11.8"OD x 2.8"H
- **LLC1116D:** 15.8"OD x 2.8"H
- **LLC1120D:** 19.7"OD x 2.8"H

Light Source:

- **LLC1112D:** UNV/21W/1260lm Del@30k/80CRI.
010V Dimming Standard
- **LLC1116D:** UNV/34W/1980lm Del@30k/80CRI.
010V Dimming
- **LLC1120D:** UNV/44W/2330lm Del@30k/80CRI.
010V Dimming Standard

Notes/Options

- EM- Provides Battery Backup in the event of a power failure.
- Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by. Dimming 10%-50%
- AAC^: Adjustable Aircraft Cables 6' Overall Height

(Only Available for LLC1120D)

Certification/Warranty

- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.
- Energy Star Rated



ORDERING INFORMATION

Model	Color Temp	Finish	Options
LLC1112D LLC1116D LLC1120D^	30K(Std)	ORB(Std) GRY*	EM- Emergency Battery Backup BI- BI-Level OCS EM/BI- EM and BI-Level AAC^ -Adjustable Air Craft Cables <i>^Only Available for LLC1120D</i>

*Special Order- MOQ and Longer Lead Times may Apply
May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information. Note: Specifications are subject to change without notice.

