

## LLDBEL-ACEM-HL

### LED DECORATIVE OUTDOOR DIE-CAST AC/EMERGENCY UNIT

#### STANDARD



#### OPTIONAL



#### ILLUMINATION

- Long lasting, efficient, ultra bright white LEDs.
- 12.0 watts (2 LEDs x 6.0 watt) per unit.
- Mirror-bright reflector and prismatic polycarbonate refractor.
- Can be used as a Normally-ON or Normally-OFF luminaire as well as on a switched circuit.
- Dissipates 1286 lumens in AC mode and 350 lumens in DC mode.

#### ELECTRICAL

- Universal 120-277 voltage.
- Change rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LEDboard for a minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-diagnostic feature performs monthly, bi-annual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- Photocell control sensor included as standard for use as dusk-to-dawn luminaire.
- Field-selectable wiring allows for AC operation of unit to be controlled using a wall-switch, photocell or other switching mechanism.

#### MOUNTING

- Universal knockout pattern on back plate for wall mount.
- Threaded opening at the top of the enclosure for conduit mount.

#### ORDERING INFORMATION

Sample Part Number: **LLDBEL-ACEM-HL-BR-SDT-PC**



#### OPTIONS

- CW: Optional internal heater for extreme cold temperature application (-30°C-50°C).
- CEC: Certified to CEC under Title 20 Regulations.


#### HOUSING

- Decorative, low profile, architectural design and Die-cast aluminum housing
- Durable powder-coated finishes in white, black, nickel and dark bronze finish.
- Sealed and gasketed.

#### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for wet locations (0°C-50°C)

#### DIMENSIONS




MODEL	HOUSING COLOR	STANDARD FEATURE	OPTIONS	STANDARD FEATURE
LLDBEL-ACEM-HL	W White	SDT Self-Diagnostics	CW Cold Weather CEC Title 20 Compliant	PC Photocell Sensor
	B Black			
	BR Dark Bronze			
	N Nickel			

## WIRE GUARDS

### WIRE GUARD

- Durable 9-gauge steel construction.
- Mounting hardware provided for easy field installation.




WG-1



## VANDAL SHIELDS

### HOUSING / MOUNTING

- High-impact resistant polycarbonate material.
- Mounting hardware provided for easy installation in the field.



BG-1

