

LLDC01XD-2G-B Series Dome Shaped Ceiling Fixture with Metal Ring and Optional Pendant Kits

Housing: Die Formed Cold Rolled Steel With Acrylic Shade.

Finish: Satin Nickel (SN) Standard.
Available by Special Order: Oil Rubbed Bronze* (ORB).

Dimensions:

- LLDC012D-2G-B[^]: 12.5"OD x 3.8"H
- LLDC014D-2G-B: 15.0"OD x 3.8"H
- LLDC016D-2G-B: 16.6"OD x 4.1"H
- LLDC018D-2G-B: 18.4"OD x 4.1"H

Light Source:



- LLDC012D-2G-B[^]: UNV/18W/1340lm Delivered@30k/80CRI. Non-Dimming
- LLDC014D-2G-B: UNV/23W/2150lm Delivered@30k/80CRI. Non-Dimming
- LLDC016D-2G-B: UNV/28W/2600lm Delivered@30k/80CRI. Non-Dimming
- LLDC018D-2G-B: UNV/35W/3250lm Delivered@30k/80CRI. Non-Dimming

Notes/Options:

- Dimming Options:
 - 010V Dimming
 - TRIAC[^] Dimming- LLDC012D-2G-B Only
- Pendant Kits add 7.0" To Height:
 - PDA: Single Stem
 - PDB: Triple Stem
- MCT - Selectable CCT 30K/35K/40K

Certification/Warranty:

- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.
- Energy Star Rated



Model	Color Temp.	Finish	Dimming	Pendant Kit
LLDC012D-2G-B [^] LLDC014D-2G-B LLDC016D-2G-B LLDC018D-2G-B	30K _(STD) 40K _(STD) 35K* 50K* MCT*	SN _(STD) ORB*	Blank=None 010V=0-10V TRIAC [^]	PDA- Single Stem PDB- Triple Stem

*Special Order- MOQ and Longer Lead Times may Apply.
May be available with other voltage, wattage, and finish options by special order.
Please contact your Lumencia Representative for more information