



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

## LLDC01XD Series

### LED Ceiling Spillring with Optional Pendant Kit

**Housing:** Die Formed Cold Rolled Steel With Acrylic Shade.

**Finish:** Satin Nickel (SN) Standard.

Available by Special Order Polished Brass\* (PB), White\* (WHT) and Oil Rubbed Bronze\* (ORB). Other Colors May Be Available by Request.

**Dimensions:**

- LLDC010D-2G: 10.4"OD x 4.2"H
- LLDC012D-2G: 11.8"OD x 4.2"H
- LLDC014D-2G: 14.5"OD x 4.6"H
- LLDC016D-2G: 16.0"OD x 4.9"H
- LLDC018D-2G: 17.8"OD x 4.9"H
- LLDC021D-2G: 20.5"OD x 5.0"H
- LLDC238D: 24.1"OD x 5.0"H

**Notes/Options:**

\*\*See Order Chart For Availability\*\*

- Non Dimming Standard
- Dimming Options:
  - 010V Dimming
  - TRIAC Dimming
- Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%. Requires Deeper Base (adds 1.0" to Height).
- EM Driver- Provides Battery Backup in the event of a power failure. Requires Deeper Base (adds 1.0" to Height). Provides 8w of Battery Backup in the event of a power failure.
- MCT - Selectable CCT 30K/35K/40K
- Pendant Kits add 7.0" To Height:
  - **PDA:** Single Stem **PDB:** Triple Stem
- Pendant Kits not Available with Deep Base.
- Deep Base Mounting Kits (**D**) Can be Ordered Separately to Maintain Profile adds 1.0" Height.



**Certification/Warranty:**

- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



\*\*Available by Special Order Only\*\*:

**LLDC10D-2G-9W:** UNV/9w/900lm Del@30k/80CRI.

Non-Dimming Standard (10.4"OD x 4.2"H). **25 Piece Minimum**

**LLDC12D-2G-9W:** UNV/9w/880lm Del@30k/80CRI.

Non-Dimming Standard (11.8"OD x 4.2"H). **25 Piece Minimum**

| Model           | Color Temp.                  | Finish   | Optional Dimming           | Mounting Kits | Type D Options<br><small>Requires Deeper Base</small> |
|-----------------|------------------------------|--|----------------------------|---------------|---|
| LLDC010D-2G-11W | UNV/11W/1000lm Del@30k/80CRI | 30K <sup>(STD)</sup><br>40K <sup>(STD)</sup><br>35K*<br>50K*<br>MCT*                 | SN <sup>(STD)</sup><br>CC* | 010V, TRIAC   | D: Deep Base  |
| LLDC010D-2G     | UNV/18W/1340lm Del@30k/80CRI |  |                            | 010V, TRIAC   |   |
| LLDC012D-2G-11W | UNV/11W/1030lm Del@30k/80CRI |  |                            | 010V, TRIAC   |   |
| LLDC238D        | UNV/40W/3450lm Del@30k/80CRI |  |                            | 010V          |   |
| LLDC012D-2G     | UNV/18W/1430lm Del@30k/80CRI | 30K <sup>(STD)</sup><br>40K <sup>(STD)</sup><br>MCT <sup>(STD)</sup><br>35K*<br>50K* | PDA<br>PDB                 | 010V, TRIAC   |   |
| LLDC014D-2G     | UNV/23W/2267lm Del@30k/80CRI |  |                            | 010V          |   |
| LLDC016D-2G     | UNV/28W/2600lm Del@30k/80CRI |  |                            | 010V          |   |
| LLDC018D-2G     | UNV/35W/3364lm Del@30k/80CRI |  |                            | 010V          |   |
| LLDC021D-2G     | UNV/40W/3500lm Del@30k/80CRI | MCT <sup>(STD)</sup>   |                            | 010V          |   |

\*Special Order- MOQ and Longer Lead Times may Apply.

May be available with other voltage, wattage, and finish options by special order. Please contact your Lumencia Representative for more information



Job Name: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Part #: \_\_\_\_\_  
 Notes: \_\_\_\_\_

## LLDC01XD JA8 Series

### JA8 Ceiling Spillring with Optional Pendant Kit

**Housing:** Die Formed Cold Rolled Steel  
 With Acrylic Shade.

**Finish:** Satin Nickel (SN) Standard.

Available by Special Order: Oil Rubbed Bronze\* (ORB).

#### Dimensions:

- **LLDC010D-2G-11W JA8:** 10.4"OD x 4.2"H
- **LLDC010D-2G JA8:** 10.4"OD x 4.2"H
- **LLDC012D-2G JA8:** 11.8"OD x 4.2"H
- **LLDC014D-2G JA8:** 14.5"OD x 4.6"H
- **LLDC016D-2G JA8:** 16.0"OD x 4.9"H

#### Light Source:

- **LLDC010D-2G-11W JA8:** 120V/11w/850lm Del@30k/90CRI.  
 TRIAC Dimming Standard.
- **LLDC010D-2G JA8:** 120V/18w/1200lm Del@30k/90CRI.  
 TRIAC Dimming Standard.
- **LLDC012D-2G JA8:** 120V/18w/1200lm Del@30k/90CRI.  
 TRIAC Dimming Standard.
- **LLDC014D-2G JA8:** UNV/24w/2000lm Del@30k/90CRI.  
 010V Dimming Standard.
- **LLDC016D-2G JA8:** UNV/30w/2300lm Del@30k/90CRI.  
 010V Dimming Standard.

#### Notes:

- LED Type: Built-in
- LM80, TM21 : 60,000 hours Rating
- LED CRI > 90 per JA8 Standard
- Flicker Free: Meets JA10 Standard
- Deep Base Mounting Kits (D) Can be Ordered Separately to Maintain Profile. Adds XX" Height.



#### Options: \*\*See Order Chart For Availability\*\*

- Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%. Requires Deeper Base (adds 1.0" to Height).
- EM Driver- Provides Battery Backup in the event of a power failure. Requires Deeper Base (adds 1.0" to Height). - Provides 8w of Battery Backup in the event of a power failure.
- Pendant Kits add 7.0" To Height:
  - PDA: Single Stem
  - PDB: Triple Stem

*Pendant Kits not Available with Deep Base.*

- Deep Base Mounting Kits (D) Can be Ordered Separately to Maintain Profile adds 1.0" Height.

#### Certification/Warranty:

- ETL/cETL Listed for Damp Locations
- CEC Meets T24 JA8
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



| Model               | Color Temp. | Finish                      | Mounting Kits                                       | Type D Options<br><small>Requires Deeper Base</small> |
|---------------------|-------------|-----------------------------|---|---|
| LLDC010D-2G-11W JA8 | 30K         | SN <sub>(STD)</sub><br>ORB* | D: Deep Base  | NONE  |
| LLDC010D-2G JA8     |             |                             |   | NONE  |
| LLDC012D-2G JA8     |             |                             | PDA   | BI, EM  |
| LLDC014D-2G JA8     |             |                             | PDB   | BI, EM, BI/EM   |
| LLDC016D-2G JA8     |             |                             | <small>Not Available with Deep Base Option.</small> |   |

\*Special Order- MOQ and Longer Lead Times may Apply.  
 May be available with other voltage, wattage, and finish options by special order. Please contact your Lumencia Representative for more information