

## LLDC01XD Series LED Ceiling Spilling with Optional Pendant Kit

**Housing:** Die Formed Cold Rolled Steel  
With Acrylic Shade.

**Finish:** Satin Nickel (SN) Standard.  
Available by Special Order Polished Brass\* (PB), White\*  
(WHT) and Oil Rubbed Bronze\* (ORB).  
Other Colors May Be Available by Request.

**Dimensions:**

- **LLDC010D-2G:** 10.4"OD x 4.2"H
- **LLDC012D-2G:** 11.8"OD x 4.2"H
- **LLDC014D-2G:** 14.5"OD x 4.6"H
- **LLDC016D-2G:** 16.0"OD x 4.9"H
- **LLDC018D-2G:** 17.8"OD x 4.9"H
- **LLDC021D-2G:** 20.5"OD x 5.0"H
- **LLDC238D:** 24.1"OD x 5.0"H

**Notes/Options:**

\*\*See Order Chart For Availability\*\*

- Non Dimming Standard
  - Dimming Options:
    - 010V Dimming
    - TRIAC Dimming
  - Bi-Level OCS- Occupancy Sensor with Multiple Settings.  
Hold Times from 5 Seconds to 20 Minutes. Stand-by  
Dimming 10%-50%. Requires Deeper Base (adds 1.0" to  
Height).
  - EM Driver- Provides Battery Backup in the event of a power  
failure. Requires Deeper Base (adds 1.0" to Height).  
Provides 8w of Battery Backup in the event of a power  
failure.
  - MCT - Selectable CCT 30K/35K/40K
  - Pendant Kits add 7.0" To Height:
    - **PDA:** Single Stem **PDB:** Triple Stem
- Pendant Kits not Available with Deep Base.*
- Deep Base Mounting Kits (**D**) Can be Ordered Separately  
to Maintain Profile adds 1.0" Height.



**Certification/Warranty:**

- ETL/cETL Listed for Damp Locations
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.
- Energy Star Rated



\*\*Available by Special Order Only\*\*:

**LLDC10D-2G-9W:** UNV/9w/900lm Del@30k/80CRI.  
Non-Dimming Standard (10.4"OD x 4.2"H). **25 Piece Minimum**  
**LLDC12D-2G-9W:** UNV/9w/880lm Del@30k/80CRI.  
Non-Dimming Standard (11.8"OD x 4.2"H).) **25 Piece Minimum**

Model	Color Temp.	Finish	Optional Dimming	Mounting Kits	Type D Options <small>Requires Deeper Base</small>	
<b>LLDC010D-2G-11W</b> UNV/11W/1000lm Del@30k/80CRI	30K <sub>(STD)</sub> 40K <sub>(STD)</sub> 35K* 50K* MCT*	SN <sub>(STD)</sub> CC*	010V, TRIAC	D: Deep Base	NONE	
<b>LLDC010D-2G</b> UNV/18W/1340lm Del@30k/80CRI			010V, TRIAC		NONE	
<b>LLDC012D-2G-11W</b> UNV/11W/1030lm Del@30k/80CRI			010V, TRIAC		BI, EM, BI/EM	
<b>LLDC238D</b> UNV/40W/3450lm Del@30k/80CRI			010V		NONE	
<b>LLDC012D-2G</b> UNV/18W/1430lm Del@30k/80CRI	30K <sub>(STD)</sub> 40K <sub>(STD)</sub> MCT <sub>(STD)</sub> 35K* 50K*			010V, TRIAC	PDA PDB <small>Not Available with Deep Base Option</small>	BI, EM, BI/EM
<b>LLDC014D-2G</b> UNV/23W/2267lm Del@30k/80CRI				010V		BI, EM, BI/EM
<b>LLDC016D-2G</b> UNV/28W/2600lm Del@30k/80CRI				010V		BI, EM, BI/EM
<b>LLDC018D-2G</b> UNV/35W/3364lm Del@30k/80CRI				010V		BI, EM, BI/EM
<b>LLDC021D-2G</b> UNV/40W/3500lm Del@30k/80CRI				MCT <sub>(STD)</sub>		010V

\*Special Order- MOQ and Longer Lead Times may Apply.  
May be available with other voltage, wattage, and finish options by special order. Please contact your Lumencia Representative for more information

## LLDC01XD JA8 Series

### JA8 Ceiling Spilling with Optional Pendant Kit

**Housing:** Die Formed Cold Rolled Steel With Acrylic Shade.

**Finish:** Satin Nickel (SN) Standard.  
Available by Special Order: Oil Rubbed Bronze\* (ORB).

**Dimensions:**

- **LLDC010D-2G-11W JA8:** 10.4"OD x 4.2"H
- **LLDC010D-2G JA8:** 10.4"OD x 4.2"H
- **LLDC012D-2G JA8:** 11.8"OD x 4.2"H
- **LLDC014D-2G JA8:** 14.5"OD x 4.6"H
- **LLDC016D-2G JA8:** 16.0"OD x 4.9"H

**Light Source:**

- **LLDC010D-2G-11W JA8:** 120V/11w/850lm Del@30k/90CRI. TRIAC Dimming Standard.
- **LLDC010D-2G JA8:** 120V/18w/1200lm Del@30k/90CRI. TRIAC Dimming Standard.
- **LLDC012D-2G JA8:** 120V/18w/1200lm Del@30k/90CRI. TRIAC Dimming Standard.
- **LLDC014D-2G JA8:** UNV/24w/2000lm Del@30k/90CRI. 010V Dimming Standard.
- **LLDC016D-2G JA8:** UNV/30w/2300lm Del@30k/90CRI. 010V Dimming Standard.

**Notes:**

- LED Type: Built-in
- LM80, TM21 : 60,000 hours Rating
- LED CRI > 90 per JA8 Standard
- Flicker Free: Meets JA10 Standard
- Deep Base Mounting Kits (D) Can be Ordered Separately to Maintain Profile. Adds XX" Height.



**Options:** \*\*See Order Chart For Availability\*\*

- Bi-Level OCS- Occupancy Sensor with Multiple Settings. Hold Times from 5 Seconds to 20 Minutes. Stand-by Dimming 10%-50%. Requires Deeper Base (adds 1.0" to Height).
- EM Driver- Provides Battery Backup in the event of a power failure. Requires Deeper Base (adds 1.0" to Height). - Provides 8w of Battery Backup in the event of a power failure.
- Pendant Kits add 7.0" To Height:
  - PDA: Single Stem
  - PDB: Triple Stem

*Pendant Kits not Available with Deep Base.*

- Deep Base Mounting Kits (D) Can be Ordered Separately to Maintain Profile adds 1.0" Height.

**Certification/Warranty:**

- ETL/cETL Listed for Damp Locations
- CEC Meets T24 JA8
- 5 Years Limited Warranty on Driver and LED
- 1 Year Warranty on Frame and Lens from Defects.



Model	Color Temp.	Finish	Mounting Kits	Type D Options <small>Requires Deeper Base</small>
LLDC010D-2G-11W JA8	30K	SN(STD) ORB*	D: Deep Base	NONE
LLDC010D-2G JA8				NONE
LLDC012D-2G JA8			PDA PDB <small>Not Available with Deep Base Option.</small>	BI, EM
LLDC014D-2G JA8				BI, EM, BI/EM
LLDC016D-2G JA8				BI, EM, BI/EM

*\*Special Order- MOQ and Longer Lead Times may Apply.  
May be available with other voltage, wattage, and finish options by special order. Please contact your Lumencia Representative for more information*