

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

### LLDLV

Dual Louvered Architectural Linear

**Housing:** Die formed 20 gauge cold-rolled steel housing. Flat steel end plate standard. (Die-cast aluminum spade end cap optional)

**Finish:** White standard; other finishes by request

**Reflector:** Die-formed white painted steel reflector standard.

**Distribution:** Up Light and Down Light


**Mounting:** Suspension Mounted. Includes aircraft cable.

#### LED & Electrical:

- 82.8 CRI Standard
- L70: >54,000 hours
- Nominal Lamp Life: 100,000 hours.
- 0-10VDC dimming 1%~100%. (Std)
- High Power Factor: 120 ~ 277 Vac input range, 50 / 60 Hz.
- Class1 or Class 2 circuit.
- Operating Temperature: 4°F (-20°C) ~ 122°F (50°C).
- <ELCU-200> Option
  - Guarantees emergency lighting remains ON or is turned on when power to the control device is lost.
  - Interfaces with fire alarm panel or security system.

#### Warranty/Certifications:

- 5 year limited warranty.
- cULus/UL listed for damp locations
- TITLE 24 Compliant.
- ARRA compliant. (optional)
- CEC Compliant EM (contact your Lumencia rep for more information)



All dimensions are in inches (millimeters).

#### Specifications: LLDLV 2', 3', 4'


Length: 24, 36, 48  
(609 / 914 / 1220)  
Width: 9 (229)  
Depth: 3 (76)  
Weight:  
LLDLV: 16.09 lbs (7.3 kg)



[ Standard ]



[ SPE option ]



[ BSC option ]

#### CONFIGURATIONS

	Model #	Input Watts	Lumen Output
4FT	46L	46W	3000 lm
	60L	56.7W	3906 lm
	72L	68.7W	4733 lm
	81L	77.7W	5354 lm

Zone	Lumens	% of Luminaire
0-40	183	3.4%
0-60	383	7.1%
0-90	683	12.8%
90-180	4672	87.2%

All dimensions are in inches (millimeters).

