Job Name:

Type:

Part #:

Notes:

LLFA277
LLFA278

Acorn Post Light

Integrated LED

- 120~277v, 50/60Hz
- Driver: UL Class2, Power Factor >.90
- Type V Distribution Standard – Optional Type III
- Ambient Operating Temperature: -40°C (-40°F) to 40°C(105°F)
- Integral Surge Suppression with option for Ground Surge Suppression

Retrofit E39 and E26

- Requires 120~277V lamp (not included)
- Lumencia offers LED E39 lamps.

Construction:

- Cast Aluminum with Stainless Steel Hardware.
- Polyester PowderCoat.
- Choice of Globes
- Fits Standard 3” Poles. LED

Certifications:

- UL Listed for Wet Locations
- Made in the USA
- RoHS

LLFA277-Tuscan

LLFA278-Doric

Part #	EPA (FT2)	Weight (LBS)	Back	Uplight	Glare
LLFA277-T	0.805	16	2	3	2
LLFA278-D	0.805	16	2	3	2

Integrated LED

- 50,000 Hour Estimated Life
- 5 Year Warranty

PART #	LIGHT SOURCE	DISTRIBUTION	CCT	FINISH	GLOBE	OPTIONS
LLFA277-T LLFA278-D	**L4000:** 40W 4000lm **L6000:** 60W 6000lm	**Blank-** Standard T5 **T3-**Type III *(Special Order)*	**40K***(Standard)* **30K***(Special Order)* **50K***(Special Order)*	**BLK-**Black **WHT-**White*(Special Order)* **BRZ-**Bronze *(Special Order)*	**P-** Clear Textured Polycarbonate **W-** White Textured Acrylic **C-** Clear Textured Acrylic **F-** Frost Textured Acrylic	**F-**Acorn Finial Topper

Ask about 0-10v Dimming

2022.01

Office: 267-438-3000 Fax: 267-288-5604
www.Lumencia.com

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED

Lumencia™
Multi-Unit Residential Lighting

Job Name:

Type:

Part #:

Retrofit E39 and E26

PART #	BASE	FINISH	GLOBE	OPTIONS	Lamps – E39 Base Only. UL Listed. 5 Year Warranty
LLFA277-T **LLFA278-D**	**E39** (Mogul Base) **E26** (Medium Base)	**BLK-**Black **WHT-**White *(Special Order)* **BRZ-**Bronze *(Special Order)*	**P-** Clear Textured Polycarbonate **W-** White Textured Acrylic **C-** Clear Textured Acrylic **F-** Frost Textured Acrylic	**F-**Acorn Finial Topper	**NL:** No Lamp (Standard) **LE39-OMNI** (E39 Base, 120~277v Type 5 Omnidirectional LED Corncob. 54w/5k/7290lm/80CRI. 360 Degree Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection) **LE39-CUTOFF** (E39 Base, 120~277v Type 5 Dark-Sky Friendly Cutoff LED Corncob. 54w/5k/5900lm/80CRI. 180 Degree Vertical Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection) **LE39-SSL** (E39 Base, 120~277v Type 3 Street Side LED Corncob. 40w/5k/5600lm/80CRI. 180 Degree Horizontal Coverage. 350 Degree Adjustable Twist Socket design. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)

2022.01

Office: 267-438-3000 Fax: 267-288-5604
www.Lumencia.com

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED