

## LLFA277 LLFA278

Acorn Post Light

### Integrated LED

- 120~277v, 50/60Hz
- Driver: UL Class2, Power Factor >.90
- Type V Distribution
- Ambient Operating Temperature: -40°C (-40°F) to 40°C(105°F)
- Integral Surge Suppression with option for Ground Surge Suppression

### Retrofit E39 and E26

- Requires 120~277V lamp (not included)
- Lumencia offers LED E39 lamps.

### Construction:

- Cast Aluminum with Stainless Steel Hardware.
- Polyester PowderCoat.
- Choice of Globes
- Fits Standard 3" Poles. LED


### Certifications:

- UL Listed for Wet Locations
- Buy American Act Compliant
- RoHS




### Integrated LED

- 50,000 Hour Estimated Life
- 5 Year Warranty



LLFA277-Tuscan



LLFA278-Doric

Part #	EPA (FT2)	Weight (LBS)	Back	Uplight	Glare
LLFA277-T	0.805	16	2	3	2
LLFA278-D	0.805	16	2	3	2

PART #	LIGHT SOURCE	CCT	FINISH	GLOBE	OPTIONS
LLFA277-T LLFA278-D	L4000: 40W 4000lm L6000: 60W 6000lm	40K(Standard) 30K(Special Order) 50K(Special Order)	BLK-Black WHT-White(Special Order) BRZ-Bronze(Special Order)	P- Clear Textured Polycarbonate W- White Textured Acrylic C- Clear Textured Acrylic F- Frost Textured Acrylic	F-Acorn Finial Topper

Ask about 0-10v Dimming



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

**Retrofit E39 and E26**

PART #	BASE	FINISH	GLOBE	OPTIONS	Lamps – E39 Base Only. UL Listed. 5 Year Warranty
<p>LLFA277-T LLFA278-D</p>	<p>E39 (Mogul Base) E26 (Medium Base)</p>	<p><b>BLK</b>-Black <b>WHT</b>-White <i>(Special Order)</i> <b>BRZ</b>-Bronze <i>(Special Order)</i></p>	<p><b>P</b>- Clear Textured Polycarbonate <b>W</b>- White Textured Acrylic <b>C</b>- Clear Textured Acrylic <b>F</b>- Frost Textured Acrylic</p>	<p>F-Acorn Finial Topper</p>	<p><b>NL</b>: No Lamp (Standard)</p> <p><b>LE39-OMNI</b> (E39 Base, 120~277v Type 5 Omnidirectional LED Corncob. 54w/5k/7290lm/80CRI. 360 Degree Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p> <p><b>LE39-CUTOFF</b> (E39 Base, 120~277v Type 5 Dark-Sky Friendly Cutoff LED Corncob. 54w/5k/5900lm/80CRI. 180 Degree Vertical Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p> <p><b>LE39-SSL</b> (E39 Base, 120~277v Type 3 Street Side LED Corncob. 40w/5k/5600lm/80CRI. 180 Degree Horizontal Coverage. 350 Degree Adjustable Twist Socket design. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p>