Lumencia
Multi-Unit Residential Lighting

Job Name:
Type:
Part #:
Notes:

LLFA293
LLFA294

Acorn Head with Large Hood

Integrated LED
- 120~277v, 50/60Hz
- Driver: UL Class2, Power Factor >.90
- Type V Distribution Standard : Optional Type III
- Ambient Operating Temperature:-40ºC(-40ºF) to +40ºC(105ºF)
- Integral Surge Suppression with option for Ground
- Surge Suppression

Retrofit E39 and E26
- Requires 120~277V lamp (not included)
- Lumencia offers LED E39 lamps.

Construction:
- Cast Aluminum with Stainless Steel Hardware.
- Polyester PowderCoat.
- Choice of Globes
- Fits Standard 3” Poles.

Certifications:
- UL Listed for Wet Locations
- Made in the USA
- RoHS

LLFA293-Tuscan



LLFA294-Doric



Part #	EPA (FT2)	Weight (LBS)	Back	Uplight	Glare
LLFA293-T	1.085	18	3	3	2
LLFA294-D	1.085	18	3	3	2

Integrated LED
- 50,000 Hour Estimated Life
- 5 Year Warranty

PART #	LIGHT SOURCE	DISTRIBUTION	CCT	FINISH	GLOBE	OPTIONS
LLFA293-T LLFA294-D	**L4000:** 40W 4000lm **L6000:** 60W 6000lm	**Blank-** Standard T5 **T3-**Type III *(Special Order)*	**40K***(Standard)* **30K***(Special Order)* **50K***(Special Order)*	**BLK-**Black **WHT-**White *(Special Order)* **BRZ-**Bronze *(Special Order)*	**P-** Clear Textured Polycarbonate **W-** White Textured Acrylic **C-** Clear Textured Acrylic **F-** Frost Textured Acrylic	N/A

Ask about 0-10v Dimming

2022.01

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED

Lumencia™
Multi-Unit Residential Lighting

Job Name:

Type:

Part #:

Notes:

Retrofit E39 and E26

PART #	BASE	FINISH	GLOBE	OPTIONS	Lamps – E39 Base Only. UL Listed. 5 Year Warranty
LLFA293-T **LLFA294-D**	**E39** (Mogul Base) **E26** (Medium Base)	**BLK**-Black **WHT**-White *(Special Order)* **BRZ**-Bronze *(Special Order)*	**P-** Clear Textured Polycarbonate **W-** White Textured Acrylic **C-** Clear Textured Acrylic **F-** Frost Textured Acrylic	**N/A**	**NL:** No Lamp (Standard) **LE39-OMNI** (E39 Base, 120~277v Type 5 Omnidirectional LED Corncob. 54w/5k/7290lm/80CRI. 360 Degree Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection) **LE39-CUTOFF** (E39 Base, 120~277v Type 5 Dark-Sky Friendly Cutoff LED Corncob. 54w/5k/5900lm/80CRI. 180 Degree Vertical Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection) **LE39-SSL** (E39 Base, 120~277v Type 3 Street Side LED Corncob. 40w/5k/5600lm/80CRI. 180 Degree Horizontal Coverage. 350 Degree Adjustable Twist Socket design. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)

Office: 267-438-3000 Fax: 267-288-5604
www.Lumencia.com

Specifications subject to change without prior notice.
© 2022 Lumencia. ALL RIGHTS RESERVED