

LLFA293 LLFA294

Acorn Head with Large Hood

Integrated LED

- 120~277V, 50/60Hz
- Driver: UL Class2, Power Factor >.90
- Type V Distribution
- Ambient Operating Temperature: -40°C(-40°F) to +40°C(105°F)
- Integral Surge Suppression with option for Ground
- Surge Suppression

Retrofit E39 and E26

- Requires 120~277V lamp (not included)
- Lumencia offers LED E39 lamps.

Construction:


- Cast Aluminum with Stainless Steel Hardware.
- Polyester PowderCoat.
- Choice of Globes
- Fits Standard 3" Poles.

Certifications:


- UL Listed for Wet Locations
- Assembled in the USA
- RoHS



LLFA293-Tuscan



LLFA294-Doric



Integrated LED

- 50,000 Hour Estimated Life
- 5 Year Warranty

Part #	EPA (FT2)	Weight (LBS)	Back	Uplight	Glare
LLFA293-T	1.085	18	3	3	2
LLFA294-D	1.085	18	3	3	2

PART #	LIGHT SOURCE	CCT	FINISH	GLOBE	OPTIONS
LLFA293-T LLFA294-D	L4000: 40W 4000lm L6000: 60W 6000lm	40K(Standard) 30K(Special Order) 50K(Special Order)	BLK-Black WHT-White (Special Order) BRZ-Bronze (Special Order)	P- Clear Textured Polycarbonate W- White Textured Acrylic C- Clear Textured Acrylic F- Frost Textured Acrylic	N/A

Ask about 0-10v Dimming



Job Name: _____

Type: _____

Part #: _____

Notes: _____

Retrofit E39 and E26

PART #	BASE	FINISH	GLOBE	OPTIONS	Lamps – E39 Base Only. UL Listed. 5 Year Warranty
LLFA293-T LLFA294-D	E39 (Mogul Base) E26 (Medium Base)	BLK-Black WHT-White <i>(Special Order)</i> BRZ-Bronze <i>(Special Order)</i>	P- Clear Textured Polycarbonate W- White Textured Acrylic C- Clear Textured Acrylic F- Frost Textured Acrylic	N/A	<p>NL: No Lamp (Standard)</p> <p>LE39-OMNI (E39 Base, 120~277v Type 5 Omnidirectional LED Corncob. 54w/5k/7290lm/80CRI. 360 Degree Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p> <p>LE39-CUTOFF (E39 Base, 120~277v Type 5 Dark-Sky Friendly Cutoff LED Corncob. 54w/5k/5900lm/80CRI. 180 Degree Vertical Coverage. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p> <p>LE39-SSL (E39 Base, 120~277v Type 3 Street Side LED Corncob. 40w/5k/5600lm/80CRI. 180 Degree Horizontal Coverage. 350 Degree Adjustable Twist Socket design. Rated For Enclosed Fixtures. IP64 Rated. 4kv Surge Protection)</p>