

LLFP103
LLFP106
LLFP109

Available in 3 profiles, 2 finishes, and 2 diffuser options.

Construction:

- Rust and Fade Resistant Composite Construction

Finishes: Black (BLK) and White

(WH) Light Sources:

- **LE8-30K:** 120V/13W/80CRI/1140LM@30K/TRIAC
- **LE8-40K:** 120V/13W/80CRI/1280LM@40K/TRIAC
- **L90U-40K:** UNV/11.3W/74CRI(TYP)/912LM@40K (Non-Dimming)
- **MB:** Requires 1 x 120V/60W Max Medium Base Lamp (Not Included)

Notes/Certification/Warranty:


- Optional Photocell (for LE8 and MB Versions only)
- Assembled in the USA
- LED Operating Temperature -40°C to +40°C
- RoHS Compliant
- Energy Star Rated When Fitted with LE8 Light Source
- cULus Listed For Wet Locations
- 5 Year Warranty on LE8 Versions
- 3 Year Warranty on L9U Version
- 1 Year Warranty on Medium Base Version



LLFP103




EXTENDS: 5 3/4"
 HCMT: 2 3/8"



LLFP106




EXTENDS: 6 1/2"
 HCMT: 2 3/8"



LLFP109



EXTENDS: 5 3/4"
 HCMT: 2 3/8"



PART #	COLOR TEMP.	FINISH	DIFFUSER	OPTIONS
LLFP103-LE8 LLFP106-LE8 LLFP109-LE8	30K 40K	BLK WH	Acrylic C-Clear Prism W- White	P-Photocell

**Energy Star Rated when fitted with LE8 Light Source*

Recommended Dimmers for LE8: LUTRON S-600H-WH, LUTRON LG-603PH-AL, LEVITON 6631-LW, LUTRON DIVA DVCL-153P, LUTRON DV6200P-WH, LUTRON SKYLARK S-600P

PART #	FINISH	DIFFUSER	OPTIONS
LLFP103-L90U-40K LLFP106-L90U-40K LLFP109-L90U-40K	BLK WH	Acrylic C-Clear Prism W- White	NA

PART #	FINISH	DIFFUSER	OPTIONS
LLFP103-MB^ LLFP106-MB^ LLFP109-MB^	BLK WH	Polycarbonate C-Clear Prism W- White	P-Photocell LWE ¹ -120v/9.5w/800lm@30K/80CRI LCE ¹ -120v/9.5w/800lm@40K/80CRI ¹ LWE and LCE Medium Base Lamps are available for purchase with the MB Light Source. UL Listed, Energy Star, Triac Dimming. Rated for 15,000 Hours. 3 Year Limited Warranty

^ Requires MOQ of 50 Pieces

Recommended Dimmers for LWE/LCE: LEVITON IPL06-10Z, LEVITON 6674, LEVITON DECORA 6672, LUTRON DVCL-153P, LUTRON DIVA VCL-153P