

LLFR121

Stagecoach Lantern Exterior Wall mount available in 3 finishes, 2 diffusers, and 2 light sources.

Construction:

- Composite Resin Construction makes for no rust or corrosion.
- Fits most 3" Poles (STD.)


Finish: Black (BLK), White (WH), and Bronze (BRZ)

Light Source:

- **LLFR121-LE8-30K:** 120V/13w/80CRI/1140LM@30K/TRIAC
- **LLFR121-LE8-40K:** 120V/13w/80CRI/1280LM@40K/TRIAC
- **LLFR121-MB:** Requires 1 x 120V/60W Max Medium Base Lamp. *(Not Included)*

Notes/Certifications/Warranty

- Optional Photocell
- Assembled in the USA
- LED Operating Temperature -40°C to +40°C
- RoHS Compliant
- cULus Listed For Wet Locations
- Energy Star Rated when fitted with the LE8 Light Source
- 5 Year Warranty on LE8 Version
- 1 Year Warranty Medium Base (MB) Version.



PART #	FINISH	DIFFUSER	OPTIONS
LLFR121-LE8-30K LLFR121-LE8-40K	BLK WH BRZ	<i>Acrylic</i> C-Clear F- Glare Free Frost	P- Photocell

**LE8 Version is Energy Star Rated*

Recommended Dimmers for LE8: LUTRON S-600H-WH, LUTRON LG-603PH-AL, LEVITON 6631-LW, LUTRON DIVA DVCL-153P, LUTRON DV6200P-WH, LUTRON SKYLARK S-600P

PART #	FINISH	DIFFUSER	OPTIONS
LLFR121-MB [^]	BLK WH BRZ	<i>Acrylic</i> C-Clear F- Glare Free Frost	P- Photocell NL- No Lamp LWE ¹ -120v/9.5w/800lm@30K/80CRI LCE ¹ -120v/9.5w/800lm@40K/80CRI ¹ LWE and LCE Medium Base Lamps are available for purchase with the Medium Base Light Source. UL Listed. Energy Star. Triac Dimming. Rated for 15,000 Hours. 3 Year Limited Warranty.

[^] Requires MOQ of 50 Pieces

Recommended Dimmers for LWE/LCE: LEVITON IPL06-10Z, LEVITON 6674, LEVITON DECORA 6672, LUTRON DVCL-153P, LUTRON DIVA VCL-153P