

Job Name: _____

Type: _____

Part #: _____

Notes: _____

LLFS112

LLFS113

Sentinel Surface Mount

Sentinel Surface Mount is available in Two Sizes and Three Diffuser Options.

Light Source:

- LE800*-120V/13W/80CRI/1140LM@3K, 1280LM@4K/TRIAC
- I140- Requires one 40W Max E26 Base Lamp. (Not Included)

Notes:

Construction:

- White Powder Coated Aluminum Pan

Listing:

- UL Listed for Wet Locations

Notable Options:


- *LLFS112 and LLFS113 are Energy Star Rated when fitted with the LE800 Light Source
- I140 requires 50 Piece MOQ
- Made in the USA
- LED Operating Temperature -40°C to +40°C

Warranty/Certifications:

- 5 Year Warranty on LE800
- 1 Year Warranty I140 Version.




LLFS112



EXTENDS: 4 1/4"
HCMT: 3 7/8"

LLFS113



EXTENDS: 4 1/2"
HCMT: 5 1/4"

PART #	LIGHT SOURCE	CCT (LED ONLY)	FINISH	DIFFUSER	OPTION
LLFS112	LE800*	W-(3K) C-(4K)	W- White	Acrylic C-Clear F-Glare Reduced Frost Prismatic	LWE ¹ -120v/9.5w/800lm@3K/90CRI Estar and Title 24 LCE ¹ -120v/9.5w/800lm@4K/80CRI Estar <small>¹LWE and LCE Medium Base Lamps are available for purchase with the I140 Light Source. UL Listed. Energy Star. Triac Dimming. Rated for 15,000 Hours. 3 Year Limited Warranty</small>
LLFS113	I140			Polycarbonate P-Clear	

Recommended Dimmers

LE Series

LUTRON S-600H-WH, LUTRON LG-603PH-AL,
LEVITON 6631-LW, LUTRON DIVA DVCL-153P,
LUTRON DV6200P-WH, LUTRON SKYLARK S-600P

LWE/LCE

LEVITON IPL06-10Z, LEVITON 6674,
LEVITON DECORA 6672, LUTRON DVCL-153P,
LUTRON DIVA VCL-153P