

## LLFT131

Tudor style wall mount with 2 light sources, 2 color options, and 3 diffusers. Optional Brass Finial Available.

**Construction:** Composite Resin Construction makes for no rust or corrosion.

### Light Source:


- **LLFT131-LE8-30K:** 120V/13w/80CRI/1140LM@30K/TRIAC
- **LLFT131-LE8-40K:** 120V/13w/80CRI/1280LM@40K/TRIAC
- **LLFT131-MB:** Requires 1 x 120V/60W Max Medium Base Lamp. (Not Included)

### Notes/Certifications/Warranty

- Optional Photocell
- Matching Post Top LLFT231
- Assembled in the USA
- LED Operating Temperature -40°C to +40°C
- RoHS Compliant
- Energy Star Rated when fitted with the LE8 light source
- cULus Listed For Wet Locations
- 3 Year Warranty on LE8 Version
- 1 Year Warranty Medium Base (MB) Version.



RoHS  
compliant



PART #	FINISH	DIFFUSER	OPTIONS
LLFT131-LE8-30K LLFT131-LE8-40K	BLK WH	Acrylic C-Clear W-White F- Glare Free Frost	P- Photocell T- Brass Finial

\*Energy Star Rated when fitted with LE8 Light Source

Recommended Dimmers for LE8: LUTRON S-600H-WH, LUTRON LG-603PH-AL, LEVITON 6631-LW, LUTRON DIVA DVCL-153P, LUTRON DV6200P-WH, LUTRON SKYLARK S-600P

PART #	FINISH	DIFFUSER	OPTIONS
LLFT131-MB <sup>^</sup>	BLK WH	Acrylic C-Clear W-White F- Glare Free Frost	NL- No Lamp P-Photocell T- Brass Finial LWE <sup>1</sup> -120v/9.5w/800lm@3K/80CRI LCE <sup>1</sup> -120v/9.5w/800lm@4K/80CRI <small><sup>1</sup>LWE and LCE Medium Base Lamps are available for purchase with the MB Light Source. UL Listed, Energy Star, Triac Dimming, Rated for 15,000 Hours. 3 Year Limited Warranty</small>

<sup>^</sup> Requires MOQ of 50 Pieces

Recommended Dimmers for LWE/LCE: LEVITON IPL06-10Z, LEVITON 6674, LEVITON DECORA 6672, LUTRON DVCL-153P, LUTRON DIVA VCL-153P

LLFT231 Matching  
Post Top



## LLFT151

Tudor style wall mount with Flemish diffuser, 2 light sources, and 2 color options. Optional Brass Finial Available.

**Construction:** Composite Resin Construction makes for no rust or corrosion.

**Light Source:**


- **LLFT151-LE8-30K:** 120V/13w/80CRI/1140LM@30K/TRIAC
- **LLFT151-LE8-40K:** 120V/13w/80CRI/1280LM@40K/TRIAC
- **LLFT151-MB:** Requires 1 x 120V/60W Max Medium Base Lamp. (Not Included)

**Notes/Certifications/Warranty**

- Optional Photocell
- Matching Post Top LLFT251
- Assembled in the USA
- LED Operating Temperature -40°C to +40°C
- RoHS Compliant
- Energy Star Rated when fitted with the LE8 light source
- cULus Listed For Wet Locations
- 3 Year Warranty on LE8 Version
- 1 Year Warranty Medium Base (MB) Version.



RoHS compliant



PART #	FINISH	DIFFUSER	OPTIONS
LLFT151-LE8-30K LLFT151-LE8-40K	BLK WH	Acrylic C-Clear Flemish	P- Photocell T- Brass Finial

\*Energy Star Rated when fitted with LE8 Light Source

Recommended Dimmers for LE8: LUTRON S-600H-WH, LUTRON LG-603PH-AL, LEVITON 6631-LW, LUTRON DIVA DVCL-153P, LUTRON DV6200P-WH, LUTRON SKYLARK S-600P

PART #	FINISH	DIFFUSER	OPTIONS
LLFT151-MB <sup>^</sup>	BLK WH	Acrylic C-Clear Flemish	NL- No Lamp P-Photocell T- Brass Finial LWE <sup>1</sup> -120v/9.5w/800lm@3K/80CRI LCE <sup>1</sup> -120v/9.5w/800lm@4K/80CRI <sup>1</sup> LWE and LCE Medium Base Lamps are available for purchase with the MB Light Source. UL Listed. Energy Star. Triac Dimming. Rated for 15,000 Hours. 3 Year Limited Warranty

<sup>^</sup> Requires MOQ of 50 Pieces

Recommended Dimmers for LWE/LCE: LEVITON IPL06-10Z, LEVITON 6674, LEVITON DECORA 6672, LUTRON DVCL-153P, LUTRON DIVA VCL-153P

LLFT251 Matching Post Top

