



Job Name: _____
Type: _____
Part #: _____
Notes: _____

LLMDF033D Wall Sconce


Construction:

- Die Formed Cold Rolled Steel.
- Standard Finish: Satin Nickel (SN).
- Shade: Acrylic
- Dimensions: 9.4"W x 10.5"H x 4.0"E



Performance:

- **LLMDF033D-22W:** UNV/22w/1800lm Delivered@3k/80CRI/Non-Dimming Standard.
- Optional 010V Dimming
- **LLMDF033D-14W:** 120v/14w/950lm Delivered@3k/80CRI/Non-Dimming Standard
- Optional Triac or 010V Dimming



Notes:

- Optional EM Driver **- Provides 4w of Battery Backup in the event of a power failure.
- Optional Bi-Level OCS **- Occupancy Sensor with Multiple Settings for Light Levels and Duration

**Fixtures are designed to accept either a Bi-Level OCS or a battery backup. We can often install both options but this may necessitate the modifications to the original fixture that will result in deeper extensions and or different lighting patterns due to extra material in the fixture body. Contact us for detailed information on the specific fixture.

Certification/Warranty:

- UL/cUL or ETL/cETL Listed
- Damp Location Rated
- 5 Year Limited Warranty on Driver and LED
- 1 Year Warranty Against Manufacturing Defects on Housing and Shade



ORDERING INFORMATION

Model	Color Temp	Finish	Options
LLMDF033D-22W	30K	SN*	Dim-Triac ¹ <small>*Triac-Dimming Only Available for the LLMDF033D-14W</small>
LLMDF033D-14W	40K		Dim- 010v EM** BI**

LLMDF033D-JA8 (UNV/22w/1580lm Delivered@3k/90CRI/0-10V Dimming) is available by Special Order. This is CEC Listed and meets Title 24 reqs. Contact your Lumencia Rep for more Information.

May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information.

Note: Specifications are subject to change without notice.