

LLMDF033D

Wall Sconce

Construction:

- Die Formed Cold Rolled Steel.
- Standard Finish: Satin Nickel (SN).
- Shade: Acrylic
- Dimensions: 9.4"W x 10.5"H x 4.0"E


Performance:

- **LLMDF033D-22W**: UNV/22w/1800lm Delivered@3k/80CRI/Non-Dimming Standard.
- Optional 010V Dimming
- **LLMDF033D-14W**: 120v/14w/950lm Delivered@3k/80CRI/Non-Dimming Standard
- Optional Triac or 010V Dimming

Notes:

- Optional EM Driver ** - Provides 4w of Battery Backup in the event of a power failure.
- Optional Bi-Level OCS ** - Occupancy Sensor with Multiple Settings for Light Levels and Duration

**Fixtures are designed to accept either a Bi-Level OCS or a battery backup. We can often install both options but this may necessitate the modifications to the original fixture that will result in deeper extensions and or different lighting patterns due to extra material in the fixture body. Contact us for detailed information on the specific fixture.



Certification/Warranty:

- UL/cUL or ETL/cETL Listed
- Damp Location Rated
- Energy Star Rated
- 5 Year Limited Warranty on Driver and LED
- 1 Year Warranty Against Manufacturing Defects on Housing and Shade



ORDERING INFORMATION

Model	Color Temp	Finish	Options
LLMDF033D-22W LLMDF033D-14W	30K 40K	SN* <small>*Oil Rubbed Bronze (ORB) by Special Order - may require MOQ and longer lead times</small>	Dim-Triac ¹ <small>¹Triac-Dimming Only Available for the LLMDF033D-14W</small> Dim- 010v EM** BI**

LLMD033D-JA8 (UNV/22w/1580lm Delivered@3k/90CRI/0-10V Dimming) is available by Special Order. This is CEC Listed and meets Title 24 reqs. Contact your Lumencia Rep for more information.

May be available in other wattages, voltages, color temperatures, finishes, and lamping sources with orders of 50 units or more. Contact your rep or the factory for more information.

Note: Specifications are subject to change without notice.