

## LLEDMPALPRO15-50

### 15-50 Watt, Premium Multi-Purpose LED Area Luminaire

#### STANDARD



#### FEATURES

- Available in 3000k (warm white), 4000k (neutral white) and 5000k (cool white) color temperatures.\*
- Long-life LEDs provide up to 372,000 hours of operation with at least 70% of initial lumen output (L<sub>70</sub>).\*\*
- Available models provide from 1,592 to 5,919 lumens, and from 110 to 125 lumens per watt (LPW).\*
- Standard optic provides an IES roadway type V distribution, or a 7V (vertical) x 7H (horizontal) NEMA floodlight distribution.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- Power factor > 90.
- Total harmonic distortion < 20%.
- Color rendering index > 80.
- Optional glare shields (full & half) & wire guards are available.
- Die cast aluminum housing with durable, dark bronze powder coat finish.
- Wireway enclosure is sealed with a water-tight, silicon rubber gasket.
- Easy installation in new construction or retrofit applications.

\* Contact factory for other color temperatures and lumen packages.  
 \*\* L70 hours are IES TM-21-11 calculated hours.



#### WARRANTY & LISTINGS

- cULus listed for wet locations in ambient temperatures from -20°C to 45°C (-4°F to 113°F).
- IP66 rated for ingress protection.
- DLC premium approved.
- Rated for 3G vibration.
- Lens is IK 8 rated for protection from external impacts.
- Salt fog tested for 1,000 hours (ASTM B117). After salt fog testing, paint rated at 9 per ASTM D1654-05 scratch test.
- Complies with FCC Part 15, class B.
- Complies with EN61000-4-5, surge immunity protection (2kV).
- 5-year warranty of all electronics and housing.

#### MOUNTING OPTIONS

- Aluminum die-cast knuckle-mount option is installed on a junction box. Includes 1/2" NPS stem with locking nut.
- Yoke-mount option provides secure attachment to flat surfaces.

#### ORDERING INFORMATION

Example: LEDMPALPRO15-K-3K

Series	Mounting Options		Color Temperature		Accessories (Order Separately)	
LEDMPALPRO15	K	Knuckle Mount	3K	3000k	LEDMPALPRO15-FGS	Full Glare Shield, 15W
LEDMPALPRO30	Y	Yoke Mount	4K	4000k	LEDMPALPRO15-HGS	Half Glare Shield, 15W
LEDMPALPRO50			5K	5000k	LEDMPALPRO15-WG	Wire Guard, 15W
					LEDMPALPRO30-FGS	Full Glare Shield, 30W
					LEDMPALPRO30-HGS	Half Glare Shield, 30W
					LEDMPALPRO30-WG	Wire Guard, 30W
					LEDMPALPRO50-FGS	Full Glare Shield, 50W
					LEDMPALPRO50-HGS	Half Glare Shield, 50W
					LEDMPALPRO50-WG	Wire Guard, 50W