

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

# DISCONTINUED

## LLPSQ

LED Area Light in 4 Wattage and 2 Distribution Options .

### Construction:

- Die cast aluminum housing in Bronze. Custom Color Available.
- Mounts to 3" Dia. pole. *2-3/8" Mount by Special Order*
- Polycarbonate lens / reflector.
- 21.16lbs (9.6kg)
- EPA: 1.044 sqft

### Performance


- Input Voltage: 120V-277V, 50/60Hz
- Choice of 40, 70, 100 or 120 Watt LED
- Power Factor: >0.95
- Color Temperature: 30/40/50 (K)
- CRI: >70
- Distribution: Type V, Type III
- Ambient Operating Temperature: -4°F (-20°C) ~ 113°F (45°C).

### Warranty/Certification

- cETLus listed. Wet Location
- LM79, LM80 available.
- 5 Year Warranty.
- L70 >50,000 hours

### Controls/Options


See Ordering Section for Complete List



PART#	LED	COLOR TEMP	DISTRIBUTION	VOLTAGE	FINISH	MOUNTING	CONTROL	OPTIONS
LLPSQ	40-40W/4080lm 70-70W/7140lm 100-100W/10000lm 120-120W/11760lm	-30K -40K -50K	T5- Type V Short T3- Type III Medium	UNV- 120-277V (Std.) HV- 347-480V	BZ- Bronze (STD.) CC-Custom Color <small>* Available custom color (RAL). Please provide us with the RAL number. * Non-standard finish with extra charge.</small>	P3- 3" Pole P2- 2.375" Pole <sup>1</sup>	BLANK- None DM-1-10V <sup>2</sup> PCUNV- Photocell-Button Type 120/277V MDS- Motion/Daylight Sensor (Hi/Low/Off)	BIRD- Bird Guard BU-EM Battery Backup RC7-NEMA 7- Wire Receptacle Only (No Controls) ARRA- Assembled in USA for Buy American Act

#### NOTES:

1. Longer lead time, please contact us for more information.
2. Only available with 40W or higher wattage options.
3. Only available with DM option.



**LLPSQ-70**

**ILLUMINANCE at a Distance**

Center Beam fc	Beam Width	1.7ft	3.4ft	2.9ft
1,144 fc	3.4 ft	304 fc	6.6 ft	5.7 ft
132 fc	10.0 ft	73.6 fc	13.4 ft	11.5 ft
48.0 fc	16.6 ft	33.1 fc	20.0 ft	17.2 ft

■ Vert. Spread: 90.1°  
■ Horiz. Spread: 81.3°

**LLPSQ-100**

**ILLUMINANCE at a Distance**

Center Beam fc	Beam Width	1.7ft	3.4ft	2.9ft
1,435 fc	3.4 ft	381 fc	6.6 ft	5.6 ft
166 fc	10.0 ft	92.4 fc	13.3 ft	11.4 ft
60.2 fc	16.5 ft	41.5 fc	19.9 ft	16.9 ft

■ Vert. Spread: 89.7°  
■ Horiz. Spread: 80.5°

**LLPSQ-120**

**ILLUMINANCE at a Distance**

Center Beam fc	Beam Width	1.7ft	3.4ft	2.9ft
1,810 fc	3.4 ft	480 fc	6.6 ft	5.7 ft
209 fc	10.0 ft	117 fc	13.4 ft	11.5 ft
75.9 fc	16.6 ft	52.3 fc	20.0 ft	17.1 ft

■ Vert. Spread: 89.9°  
■ Horiz. Spread: 81.1°

Optional MDS Sensor- Default Settings	
Detection Sensitivity	100%
Hold Time	90s
Day Light Sensor	Disable or 50lux
Stand by Time	10min
Stand by Dimming Level	10%