



Job Name: _____

Type: _____

Part #: _____

Notes: _____

LLPUFF

LED Puff Light Available in 3 sizes.

Lens: Vacuum formed, non-yellowing, smooth, white acrylic.

Body Material: Die-formed from heavy gauge steel, finished in a baked white enamel or polyester powder coating.

Dimensions:

1x4: 8.00" Base Width x 11.50" Lens Width x 51.50" Length x 4.75" Total Height

2x2: 21.68" Base Width x 27.00" Lens Width x 27.50" Length x 4.75" Total Height

2x4: 21.68" Base Width x 27.00" Lens Width x 51.50" Length x 4.75" Total Height

Electrical:

- 120-277V (Universal Voltage)
- Dial in Lumens - select a lumen output between 3200lm and 11800lm
- Available in 30K/35K/40K/50K
- 0-10v low voltage dimming standard per fixture
- CRI >80 (>90 AVAILABLE UPON REQUEST)
- Power Factor (PF) greater than or equal to 0.90
- Maximum Total Harmonic Distortion (THD) less than 20%

Mounting: Knockouts and holes for both surface and pendant mounting.

Notes/Certifications/Warranty:

- Operates for at least 50,000 hours at maximum case temperature and 90% non-condensing relative humidity.
- Withstands Category A surges of 4 kV without impairment performance.
- Integral thermal protection that reduces the output power to protect the driver and light source from damage if the case temperature approaches or exceeds the driver's maximum operating temperature.
- 47 CFR 15. Complies with the requirements of the Federal Communications Commission (FCC) rules and regulations
- Non-Consumer (Class A) for EMI/RFI(conducted and radiated)
- Class A sound rating.
- Restriction of Hazardous Substances (RoHS) compliant.
- UL Listed Class P thermally protected led drivers.
- Comply with National Energy Standard.
- All units are UL certified damp location.
- 50,000 hours of L70 LED Life
- 5-year warranty of all electronics and housing.



Standard Lumen Packages

1X4 & 2X4

- 3220 (17W)
- 4480 (24W)
- 5705 (30W)
- 6910 (37W)
- 8640 (48W)
- 11797 (70W)

2X2

- 3166 (17W)
- 4350 (24W)
- 5470 (31W)
- 6452 (39W)

Ordering Information

PART #	LENGTH	LUMENS	COLOR TEMP	OPTIONS
LLPUFF Drop Ceiling Flanged	1x4 2x2 2x4	LMxxxxx: Select a lumen output between 3200 and 11800	30K 35K 40K 50K	EM: Emergency driver SQL: Square lens PLF: Puff Lens FR: Frosted Lens over LED Board OCS: Bi-Level Occupancy Sensor 9CRI: 90 CRI